



Twin Unswitched White A
Rated RCD Socket


Twin Unswitched White A Rated RCD Socket

DESCRIPTION

Simple to install 2-gang unswitched passive RCD socket with durable metal clad exterior, perfect for providing local electrical protection in garages, workshops or warehouses

FEATURES

- Highly stable and reliable polycarbonate construction, with raised square profile and screwed faceplate
- Type A rated to ensure tripping for residual a.c. currents and pulsating d.c. currents
- 13A fused spur with “passive” 30mA RCD protection at less than 40ms (typical)
- Complete with TEST button
- Twin earth terminals for easy cable connections
- Mechanical latching (no need to reset after power loss)



GENERAL INFORMATION

Colour / Finish	White	Application	Internal
Product Warranty	1 Year	Net Weight	0.27 kg

TECHNICAL INFORMATION

Construction Materials Line 1	Polycarbonate	Dimensions - Height	86 mm
Dimensions - Width	38 mm	Dimensions - Depth	146 mm



Product Code	Description	Item Barcode
TWSARCDWH	Twin Unswitched White A Rated RCD Socket	5013845000130

PACKAGING	
Packaging Type	Colour Box
Individual unit gross weight	310 g
Intermediate Carton Depth (mm)	170 mm
Intermediate Carton Width (mm)	270 mm
Intermediate Carton Height (mm)	110 mm
Intermediate Pack Qty.	5
Pallet Qty	0
MOM / OPQ	1 / 40

