Spec Sheet VECO6WPTW2











DESCRIPTION

Weatherproof

The range of economic LED weatherproof battens comes complete with a polycarbonate opal diffuser for even distribution and push fit terminal connections, cable entries from the rear and end of the fitting provided with surface mount brackets and suspension hooks

FEATURES

- · Polycarbonate diffuser & ABS housing
- · Multiple fixing options supplied with surface mounting brackets and suspension hooks
- Push fit terminal connections
- Temporary suspension option for easy installation
- · Cable entries on end and back of fitting



5ft Single
5ft Twin [] [] [] [] [] [] [] [] [] [
6ft Single & Twin 1800mm (6ft) 100mm

GENERAL INFORMATION			
Light Source	LED	Colour / Finish	Grey
Application	Internal/External	Mounting Type	Surface, Suspended
Product Warranty	5 Years	Net Weight	1.8 kg
Energy Efficiency Class	Е		

TECHNICAL INFORMATION			
Nominal Voltage	240 V	Frequency	50Hz
Class Protection	1	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	40,000 h
Number of switching cycles	15,000	Construction Materials Line 1	ABS
Construction Materials Line 2	PC	Dimensions - Height	68 mm
Dimensions - Width	100 mm	Dimensions - Depth	1800 mm

PRODUCT INFORMATION			
Wattage Combined	65W	CCT Combined	4000K
Luminaire Lumens Combined	6200 lm	lm/W Combined	95 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
IP Rating	IP65		















PHOTOMETRICS					
Product Code	Product Type	Watts	сст	Luminaire lumens	Lm/W
VECO5WPSI2	Standard	30 W	4000 K	2900 lm	97 lm/W
VECO5WPTW2	Standard	45 W	4000 K	4300 lm	96 lm/W
VECO6WPSI2	Standard	48 W	4000 K	4500 lm	94 lm/W
VECO6WPTW2	Standard	65 W	4000 K	6200 lm	95 lm/W

PACKAGING		
Packaging Type	Plain Box	
Individual unit gross weight	2,215 g	
Pallet Qty	0	
MOM / OPQ	1/6	





