



6FT Twin Economy LED Weatherproof


6ft 65W 4000K Twin Economy LED Weatherproof

DESCRIPTION

The range of economic LED weatherproof battens comes complete with a polycarbonate opal diffuser for even distribution and push fit terminal connections, cable entries from the rear and end of the fitting provided with surface mount brackets and suspension hooks

FEATURES

- Polycarbonate diffuser & ABS housing
- Multiple fixing options - supplied with surface mounting brackets and suspension hooks
- Push fit terminal connections
- Temporary suspension option for easy installation
- Cable entries on end and back of fitting



GENERAL INFORMATION

Light Source	LED	Colour / Finish	Grey
Application	Internal/External	Mounting Type	Surface, Suspended
Product Warranty	5 Years	Net Weight	1.8 kg
Energy Efficiency Class	E		

TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50Hz
Class Protection	1	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	40,000 h
Number of switching cycles	15,000	Construction Materials Line 1	ABS
Construction Materials Line 2	PC	Dimensions - Height	68 mm
Dimensions - Width	100 mm	Dimensions - Depth	1800 mm
IP Rating	IP65		

PRODUCT INFORMATION

Wattage Combined	65W	CCT Combined	4000K
Luminaire Lumens Combined	6200 lm	lm/W Combined	95 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7



Dimmable	Not Dimmable	CCTI/WATTI: Rated Peak Intensity	1,757 cd
----------	--------------	----------------------------------	----------



IP65





IP65

PHOTOMETRICS					
Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
VECO5WPSI2	5ft, Single	30 W	4000 K	2900 lm	97 lm/W
VECO5WPTW2	5ft, Twin	45 W	4000 K	4300 lm	96 lm/W
VECO6WPSI2	Standard	48 W	4000 K	4500 lm	94 lm/W
VECO6WPTW2	Standard	65 W	4000 K	6200 lm	95 lm/W

PACKAGING	
Packaging Type	Plain Box
Individual unit gross weight	2,215 g
Pallet Layer Qty	24
Pallet Layers	5
Pallet Qty	120
MOM / OPQ	1 / 6

