Spec Sheet VECOBAT6FT









6ft 32W 4000K LED Economy Batten Fitting

DESCRIPTION

6ft LED highly efficient economy batten fixture, slim profile design with even light distribution, front diffuser and end caps removable to allow for easy wiring at either end of the batten or Besa mounting from the rear of the fitting, available in both standard and high output mode to suit different ceiling heights and task requirements

FEATURES

- LED tray can be removed from the housing for easy installation $% \left(1\right) =\left(1\right) \left(1\right) +\left(1\right) \left(1\right) \left(1\right) +\left(1\right) \left(1\right) \left(1\right) \left(1\right) +\left(1\right) \left(1\right)$
- · 20mm knockout glands at each end for through wiring options
- · BESA box mounting
- Gear tray retaining straps
- Up to 106 lm/W
- Pressed steel body and polycarbonate diffuser



4FT (1185mm) 5FT (1480mm) 6FT (1750mm)

GENERAL INFORMATION			
Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Surface, Suspended
Product Warranty	5 Years	Net Weight	2.13 kg

TECHNICAL INFORMATION			
Nominal Voltage	240 V	Frequency	50Hz
Class Protection	1	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	40 °C	Average Rated Life	30,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Steel
Construction Materials Line 2	Polycarbonate diffuser	Dimensions - Height	65 mm
Dimensions - Width	57 mm	Dimensions - Depth	1750 mm

PRODUCT INFORMATION			
Wattage Combined	32W	CCT Combined	4000K
Luminaire Lumens Combined	4096 lm	lm/W Combined	128 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.8
IP Rating	IP20		













PHOTOMETRICS					
Product Code	Product Type	Watts	ССТ	Luminaire lumens	Lm/W
VECOBAT4FT	Non-Dimmable, 4ft	18 W	4000 K	2456 lm	136 lm/W
VECOBAT5FT	Non-Dimmable, 5ft	24 W	4000 K	3124 lm	130 lm/W
VECOBAT5HO	Non-Dimmable, 5ft	48 W	4000 K	4000 lm	83 lm/W
VECOBAT6FT	Non-Dimmable, 6ft	32 W	4000 K	4096 lm	128 lm/W
VECOBAT6HO	Non-Dimmable, 6ft	64 W	4000 K	7997 lm	125 lm/W

H	2	20

PACKAGING		
Packaging Type	Plastic Shrink Wrap	
Individual unit gross weight	1,540 g	
Pallet Layer Qty	24	
Pallet Layers	8	
Pallet Qty	192	
MOM / OPQ	6 / 6	







