



Plastic LED Under Cabinet Light


Triangle Plastic LED Under Cabinet Light

DESCRIPTION

Polycarbonate Construction

FEATURES

- 3000K Warm White Colour Temperature: Offering a pleasing lighting appearance
- 2W = 100 lumens: ideal low energy solution to standard halogen cabinet lights
- Not suitable for use with dimmers
- Not suitable for recessed installation
- Pre-wired with 2m mains cable and no separate driver required: facilitating easy installation



GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	0.26 kg
Energy Efficiency Class	G		

TECHNICAL INFORMATION

Nominal Voltage	240 V	Frequency	50Hz
Class Protection	2	Average Rated Life	30,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Polycarbonate
Dimensions - Height	140 mm	Dimensions - Width	122 mm
Dimensions - Depth	40 mm		

PRODUCT INFORMATION

Wattage Combined	2W	CCT Combined	3000K
Luminaire Lumens Combined	100 lm	lm/W Combined	50 lm/w
Beam Angle	90°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
IP Rating	IP20		





IP20

PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
VECOABPCI	Standard	2 W	3000 K	100 lm	50 lm/W
VECOABPTR	Standard	2 W	3000 K	100 lm	50 lm/W

PACKAGING

Packaging Type	Plain Box
Individual unit gross weight	165 g
Pallet Qty	0
MOM / OPQ	1 / 100

