



Compact Emergency LED Exitbox

Maintained or non-maintained Exit box 4W LED 6000K with ISO 7010 up legend

DESCRIPTION

Low energy compact alternative to standard emergency exit signs, robust steel construction with traditional battery test button for easy access, suitable to be adjusted for non-maintained operation to suit a number of commercial and industrial applications

FEATURES

- Push fit terminals
- 3 hour maintained mode as standard which can also be configured for non maintained operation. Facility for remote switching
- LED charge light and battery test button
- Full range of interchangeable polycarbonate ISO 7010 legends available (VECOISO range), comes complete with up arrow legend
- Diffuser on base: for added downward illumination of exit path
- Viewing distance: 29m
- Li-Ion 3.2V 1500mAh battery 5 year warranty – Replacement battery code: EB17

GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Battery Warranty	5 Years
Net Weight	0.75 kg		

TECHNICAL INFORMATION

Nominal Voltage	240 V	Frequency	50Hz
Class Protection	1	Average Rated Life	30,000 h
Construction Materials Line 1	Polycarbonate	Dimensions - Height	180 mm
Dimensions - Width	300 mm	Dimensions - Depth	40 mm
IP Rating	IP20		

PRODUCT INFORMATION

Wattage Combined	4W	CCT Combined	6200K
Luminaire Lumens Combined	70 lm	lm/W Combined	18 lm/w
Beam Angle	120°	Dimmable	Not Dimmable
CCTI/WATTI: Rated Peak Intensity	40 cd		





PHOTOMETRICS					
Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
VECOEXIT3M	Emergency	4 W	6200 K	70 lm	18 lm/W

ACCESSORIES		
Product Code	Description	MOM / OPQ
EB17	Li-Ion 3.2V 1500mAh Stick Battery	1 / 100
EB25	Li-Ion 3.2V 1000mAh Stick Battery	1 / 10
VECOISOD	Down Legend for Compact EM3 Exitbox	1 / 100
VECOISOL	Left Legend for Compact EM3 Exitbox	1 / 100
VECOISOR	Right Legend for Compact EM3 Exitbox	1 / 100

PACKAGING	
Packaging Type	Plain Box
Individual unit gross weight	756 g
Pallet Layer Qty	140
Pallet Layers	3
Pallet Qty	420
MOM / OPQ	1 / 20

