



Compact Emergency LED  
Exitbox

Maintained or non-maintained Exit box 4W  
LED 6000K with ISO 7010 up legend

DESCRIPTION

Low energy compact alternative to standard emergency exit signs, robust steel construction with traditional battery test button for easy access, suitable to be adjusted for non-maintained operation to suit a number of commercial and industrial applications

FEATURES

- Push fit terminals
- 3 hour maintained mode as standard which can also be configured for non maintained operation. Facility for remote switching
- LED charge light and battery test button
- Full range of interchangeable polycarbonate ISO 7010 legends available (VECOISO range), comes complete with up arrow legend
- Diffuser on base: for added downward illumination of exit path
- Viewing distance: 29m
- Li-Ion 3.2V 1500mAh battery 5 year warranty - Replacement battery code: EB17

GENERAL INFORMATION

|                  |          |                  |         |
|------------------|----------|------------------|---------|
| Light Source     | LED      | Colour / Finish  | White   |
| Application      | Internal | Mounting Type    | Surface |
| Product Warranty | 5 Years  | Battery Warranty | 5 Years |
| Net Weight       | 0.75 kg  |                  |         |

TECHNICAL INFORMATION

|                               |               |                     |          |
|-------------------------------|---------------|---------------------|----------|
| Nominal Voltage               | 240 V         | Frequency           | 50Hz     |
| Class Protection              | 1             | Average Rated Life  | 30,000 h |
| Construction Materials Line 1 | Polycarbonate | Dimensions - Height | 180 mm   |
| Dimensions - Width            | 300 mm        | Dimensions - Depth  | 40 mm    |

PRODUCT INFORMATION

|                           |       |               |         |
|---------------------------|-------|---------------|---------|
| Wattage Combined          | 4W    | CCT Combined  | 6200K   |
| Luminaire Lumens Combined | 70 lm | lm/W Combined | 18 lm/w |
| Beam Angle                | 120°  | IP Rating     | IP20    |



## PHOTOMETRICS

| Product Code | Product Type | Watts | CCT    | Luminaire lumens | Lm/W    |
|--------------|--------------|-------|--------|------------------|---------|
| VECOEXIT3M   | Emergency    | 4 W   | 6200 K | 70 lm            | 18 lm/W |

## ACCESSORIES

| Product Code | Description                          | MOM / OPQ |
|--------------|--------------------------------------|-----------|
| EB17         | Li-Ion 3.2V 1500mAh Stick Battery    | 1 / 100   |
| EB25         | Li-Ion 3.2V 1000mAh Stick Battery    | 1 / 10    |
| VECOISOD     | Down Legend for Compact EM3 Exitbox  | 1 / 100   |
| VECOISOL     | Left Legend for Compact EM3 Exitbox  | 1 / 100   |
| VECOISOR     | Right Legend for Compact EM3 Exitbox | 1 / 100   |

## PACKAGING

|                              |           |
|------------------------------|-----------|
| Packaging Type               | Plain Box |
| Individual unit gross weight | 756 g     |
| Pallet Layer Qty             | 140       |
| Pallet Layers                | 3         |
| Pallet Qty                   | 420       |
| MOM / OPQ                    | 1 / 20    |

