



Economy 20W Floodlight with PIR


Economy IP44 Floodlight 20W LED 1700lm 4000K with PIR

DESCRIPTION

Economy 20W Floodlight with PIR

FEATURES

- Aluminium body with tempered glass diffuser
- Pre-wired with 30cm flex
- Quick fix bracket
- Vertically and horizontally adjustable PIR
- Time on adjustment 10 seconds to 10 minutes
- 8 metre detection range
- Lux level adjustments: 10 Lux to 2000 Lux
- 120° detection angle



GENERAL INFORMATION

| | | | |
|-------------------------|----------|-----------------|---------|
| Light Source | LED | Colour / Finish | Black |
| Application | External | Mounting Type | Surface |
| Product Warranty | 5 Years | Net Weight | 0.40 kg |
| Energy Efficiency Class | E | | |

TECHNICAL INFORMATION

| | | | |
|-------------------------------|--------|-------------------------------|-----------|
| Nominal Voltage | 240 V | Frequency | 50Hz |
| Class Protection | 1 | Average Rated Life | 25,000 h |
| Number of switching cycles | 12,500 | Construction Materials Line 1 | Aluminium |
| Construction Materials Line 2 | PC | Dimensions - Height | 98 mm |
| Dimensions - Width | 132 mm | Dimensions - Depth | 26 mm |

PRODUCT INFORMATION

| | | | |
|---------------------------|---------|-------------------|---------|
| Wattage Combined | 20W | CCT Combined | 4000K |
| Luminaire Lumens Combined | 1700 lm | lm/W Combined | 85 lm/w |
| Beam Angle | 120° | CRI | 80 |
| SDCM | <6 | Lumen Maintenance | 0.7 |
| IP Rating | IP44 | | |





IP44

PHOTOMETRICS

| Product Code | Product Type | Watts | CCT | Luminaire lumens | Lm/W |
|--------------|--------------|-------|--------|------------------|---------|
| VECOF10PIR | PIR | 10 W | 4000 K | 850 lm | 85 lm/W |
| VECOF20PIR | PIR | 20 W | 4000 K | 1700 lm | 85 lm/W |
| VECOF30PIR | PIR | 30 W | 4000 K | 2500 lm | 83 lm/W |
| VECOF50PIR | PIR | 50 W | 4000 K | 4250 lm | 85 lm/W |
| VECOFLD10 | Standard | 10 W | 4000 K | 850 lm | 85 lm/W |
| VECOFLD50 | Standard | 50 W | 4000 K | 4250 lm | 85 lm/W |

PACKAGING

| | |
|---------------------------------|-----------|
| Packaging Type | Plain Box |
| Individual unit gross weight | 380 g |
| Intermediate Carton Depth (mm) | 195 mm |
| Intermediate Carton Width (mm) | 300 mm |
| Intermediate Carton Height (mm) | 315 mm |
| Intermediate Pack Qty. | 10 |
| Pallet Qty | 0 |
| MOM / OPQ | 1 / 40 |

