
Spec Sheet VECOFLD10

5 Year Warranty

IP65





Economy 10W LED Floodlight

Economy IP65 Floodlight 10W LED 850lm 4000K

DESCRIPTION

Economy 10W Floodlight

FEATURES

- Aluminium body with tempered glass diffuser
- Pre-wired with 30cm flex
- Quick fix bracket

GENERAL INFORMATION			
Light Source	LED	**Colour / Finish**	Black
Application	External	**Mounting Type**	Surface
Product Warranty	5 Years	**Net Weight**	0.22 kg
Energy Efficiency Class	F		

TECHNICAL INFORMATION			
Nominal Voltage	240	**Frequency**	50Hz
Class Protection	1	**Average Rated Life**	25,000 h
Number of switching cycles	12,500	**Construction Materials Line 1**	Aluminium
Construction Materials Line 2	PC	**Dimensions - Height**	76 mm
Dimensions - Width	100 mm	**Dimensions - Depth**	25 mm
IP Rating	IP65		

PRODUCT INFORMATION			
Wattage Combined	10W	**CCT Combined**	4000K
Luminaire Lumens Combined	850 lm	**lm/W Combined**	85 lm/w
Beam Angle	110°	**CRI**	80
SDCM	<6	**Lumen Maintenance**	0.7
Dimmable	Not Dimmable	**CCT1/WATT1: Rated Peak Intensity**	350 cd

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

PHOTOMETRICS					
Product Code	**Product Type**	**Watts**	**CCT**	**Luminaire lumens**	**Lm/W**
VECOF10PIR	PIR	10 W	4000 K	850 lm	85 lm/W
VECOF20PIR	PIR	20 W	4000 K	1700 lm	85 lm/W
VECOF30PIR	PIR	30 W	4000 K	2500 lm	83 lm/W
VECOF50PIR	PIR	50 W	4000 K	4250 lm	85 lm/W
VECOFLD10	Standard	10 W	4000 K	850 lm	85 lm/W
VECOFLD50	Standard	50 W	4000 K	4250 lm	85 lm/W

PACKAGING	
Packaging Type	Plain Box
Individual unit gross weight	229 g
Intermediate Carton Depth (mm)	140 mm
Intermediate Carton Width (mm)	195 mm
Intermediate Carton Height (mm)	210 mm
Intermediate Pack Qty.	10
Pallet Layer Qty	400
Pallet Layers	5
Pallet Qty	2,000
MOM / OPQ	1 / 40