



Economy 50W LED Floodlight


Economy IP65 Floodlight 50W LED 4250lm
4000K

DESCRIPTION

Economy 50W Floodlight

FEATURES

- Aluminium body with tempered glass diffuser
- Pre-wired with 30cm flex
- Quick fix bracket



GENERAL INFORMATION

Light Source	LED	Colour / Finish	Black
Application	External	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	0.78 kg
Energy Efficiency Class	F		

TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50Hz
Class Protection	1	Average Rated Life	25,000 h
Number of switching cycles	12,500	Construction Materials Line 1	Aluminium
Construction Materials Line 2	PC	Dimensions - Height	160 mm
Dimensions - Width	218 mm	Dimensions - Depth	28 mm
IP Rating	IP65		

PRODUCT INFORMATION

Wattage Combined	50W	CCT Combined	4000K
Luminaire Lumens Combined	4250 lm	lm/W Combined	85 lm/w
Beam Angle	110°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
Dimmable	Not Dimmable	CCTI/WATT1: Rated Peak Intensity	1,749 cd





PHOTOMETRICS					
Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
VECOF10PIR	PIR	10 W	4000 K	850 lm	85 lm/W
VECOF20PIR	PIR	20 W	4000 K	1700 lm	85 lm/W
VECOF30PIR	PIR	30 W	4000 K	2500 lm	83 lm/W
VECOF50PIR	PIR	50 W	4000 K	4250 lm	85 lm/W
VECOFLD10	Standard	10 W	4000 K	850 lm	85 lm/W
VECOFLD50	Standard	50 W	4000 K	4250 lm	85 lm/W

PACKAGING	
Packaging Type	Plain Box
Individual unit gross weight	854 g
Intermediate Carton Depth (mm)	220 mm
Intermediate Carton Width (mm)	245 mm
Intermediate Carton Height (mm)	375 mm
Intermediate Pack Qty.	10
Pallet Qty	0
MOM / OPQ	1 / 20

