



Economy LED IP65 Fire Rated Downlight 3000K


IP65 fire rated dimmable downlight 5W LED 3000K chrome bezel with satin nickel and white bezel options

DESCRIPTION

Economy LED IP65 Fire Rated Downlight

FEATURES

- Fire rated tested for individual 30, 60 and 90 min ceiling types. Foam bezel seals against air permeability
- Integrated chrome bezel with additional Satin nickel and white bezels also included
- Dimmable - for optimum dimming performance we recommend using a compatible LED dimmer
- Pressed steel construction
- 60° beam angle
- Push terminals
- Hole cut out dimension - 60mm
- Insulation bracket available separately - VECOIBRACK



GENERAL INFORMATION

Light Source	LED	Colour / Finish	Stainless Steel
Application	Internal	Mounting Type	Recessed
Product Warranty	5 Years	Net Weight	0.2 kg
Energy Efficiency Class	E		

TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50Hz
Class Protection	2	Average Rated Life	36,000 h
Number of switching cycles	15,000	Construction Materials Line 1	ABS
Construction Materials Line 2	PC	Dimensions - Height	78 mm
Dimensions - Width	84 mm	Dimensions - Depth	84 mm
IP Rating	IP65		

PRODUCT INFORMATION

Wattage Combined	5W	CCT Combined	3000K
Luminaire Lumens Combined	540 lm	lm/W Combined	108 lm/w
Beam Angle	60°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
Lighting Technology used	LED	Non-Directional or Directional	DLS



Mains or non-mains	MLS	Connected light source (CLS)	FALSE
Colour tuneable light source	FALSE	High Luminance light source	FALSE
Anti Glare shield	FALSE	Dimmable	Not Dimmable
CCT1/WATT1: Rated Peak Intensity	286 cd		



IP65





IP65

PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
VECOIFIRE3	Standard	5 W	3000 K	540 lm	108 lm/W
VECOIFIRE4	Standard	5 W	4000 K	560 lm	112 lm/W

PACKAGING

Packaging Type	Plain Box
Individual unit gross weight	207 g
Pallet Layer Qty	240
Pallet Layers	6
Pallet Qty	1,440
MOM / OPQ	1 / 40

