

4W Economy T5 LED Linkable Fitting


4W Economy T5 LED Linkable Fitting

DESCRIPTION

Economy T5 LED Linkable Fitting

FEATURES

- Superb light output and lighting effect - low power consumption with enhanced life expectancy
- 1.8m mains lead with 0.22m link lead
- Linkable with up to 5 other fittings
- Optically optimised diffuser
- Ensures a soft diffused light with no degradation of light output
- Rocker switch



GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	0.18 kg
Energy Efficiency Class	E		

TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50-60Hz
Class Protection	2	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	30,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Polycarbonate
Dimensions - Height	30 mm	Dimensions - Width	322 mm
Dimensions - Depth	22 mm	IP Rating	IP20

PRODUCT INFORMATION

Wattage Combined	4W	CCT Combined	4000K
Luminaire Lumens Combined	460 lm	lm/W Combined	115 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
Lighting Technology used	LED	Non-Directional or Directional	NDLS





Mains or non-mains	MLS	Connected light source (CLS)	FALSE
Colour tuneable light source	FALSE	High Luminance light source	FALSE
Anti Glare shield	FALSE	Dimmable	Not Dimmable
Correlated Colour temperature type	SINGLE_VALUE	Correlated Colour temperature (K) 1	4,000
Chromaticity coordinates x	0.4415	Chromaticity coordinates y	0.404
Stroboscopic effect metric (SVM)	0	Flicker Metric (pst)	0
R9 colour rendering index	13	Survival factor @6000hrs	1
Spectrum report available	Yes	Displacement Factor	0.84
CCTI/WATTI: Rated Peak Intensity	260 cd		





IP20

PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
VECOLT510	Standard	10 W	4000 K	1150 lm	115 lm/W
VECOLT514	Standard	14 W	4000 K	1610 lm	115 lm/W
VECOLT54	Standard	4 W	4000 K	460 lm	115 lm/W
VECOLT58	Standard	8 W	4000 K	920 lm	115 lm/W

PACKAGING

Packaging Type	Plain Box
Individual unit gross weight	222 g
Pallet Layer Qty	360
Pallet Layers	4
Pallet Qty	1,440
MOM / OPQ	1 / 30

