

8W Economy T5 LED Linkable Fitting


8W Economy T5 LED Linkable Fitting

DESCRIPTION

Economy T5 LED Linkable Fitting

FEATURES

- Superb light output and lighting effect - low power consumption with enhanced life expectancy
- 1.8m mains lead with 0.22m link lead
- Linkable with up to 5 other fittings
- Optically optimised diffuser
- Ensures a soft diffused light with no degradation of light output
- Rocker switch



GENERAL INFORMATION

| | | | |
|-------------------------|----------|-----------------|---------|
| Light Source | LED | Colour / Finish | White |
| Application | Internal | Mounting Type | Surface |
| Product Warranty | 5 Years | Net Weight | 0.2 kg |
| Energy Efficiency Class | E | | |

TECHNICAL INFORMATION

| | | | |
|-----------------------------|--------|-------------------------------|---------------|
| Nominal Voltage | 240 | Frequency | 50-60Hz |
| Class Protection | 2 | Operating Temperature (Min) | -20 °C |
| Operating Temperature (Max) | 45 °C | Average Rated Life | 30,000 h |
| Number of switching cycles | 15,000 | Construction Materials Line 1 | Polycarbonate |
| Dimensions - Height | 30 mm | Dimensions - Width | 585 mm |
| Dimensions - Depth | 22 mm | IP Rating | IP20 |

PRODUCT INFORMATION

| | | | |
|---------------------------|--------|--------------------------------|----------|
| Wattage Combined | 8W | CCT Combined | 4000K |
| Luminaire Lumens Combined | 920 lm | lm/W Combined | 115 lm/w |
| Beam Angle | 120° | CRI | 80 |
| SDCM | <6 | Lumen Maintenance | 0.7 |
| Lighting Technology used | LED | Non-Directional or Directional | NDLS |





| | | | |
|------------------------------------|--------------|-------------------------------------|--------------|
| Mains or non-mains | MLS | Connected light source (CLS) | FALSE |
| Colour tuneable light source | FALSE | High Luminance light source | FALSE |
| Anti Glare shield | FALSE | Dimmable | Not Dimmable |
| Correlated Colour temperature type | SINGLE_VALUE | Correlated Colour temperature (K) 1 | 4,000 |
| Chromaticity coordinates x | 0.441 | Chromaticity coordinates y | 0.404 |
| Stroboscopic effect metric (SVM) | 0.0 | Flicker Metric (pst) | 0.0 |
| R9 colour rendering index | 14.0 | Survival factor @6000hrs | 1.0 |
| Claim LED Replace Fluorescent | FALSE | Spectrum report available | Yes |
| Displacement Factor | 0.84 | CCT1/WATT1: Rated Peak Intensity | 260 cd |





| PHOTOMETRICS | | | | | |
|--------------|--------------|-------|--------|------------------|----------|
| Product Code | Product Type | Watts | CCT | Luminaire lumens | Lm/W |
| VECOLT510 | Standard | 10 W | 4000 K | 1150 lm | 115 lm/W |
| VECOLT514 | Standard | 14 W | 4000 K | 1610 lm | 115 lm/W |
| VECOLT54 | Standard | 4 W | 4000 K | 460 lm | 115 lm/W |
| VECOLT58 | Standard | 8 W | 4000 K | 920 lm | 115 lm/W |

| PACKAGING | |
|------------------------------|-----------|
| Packaging Type | Plain Box |
| Individual unit gross weight | 279 g |
| Pallet Layer Qty | 240 |
| Pallet Layers | 4 |
| Pallet Qty | 960 |
| MOM / OPQ | 1 / 30 |

