





VECOMEM3

Maintained IP65 Emergency rectangular bulkhead 4W LED 6400K

FEATURES

- Polycarbonate construction
- Hinged gear tray & push fit terminals
- 20mm gland entries as standard
- Facility for remote switching and non-maintained mode
- 270 lm when connected to mains, 130 lm when connected to battery
- 20m viewing distance
- Minimum 3 hour functionality in emergency mode
- Ni-Cd 3.6V 800mAh battery 1 year warranty - Replacement battery code: EB21



GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal/External	Mounting Type	Surface
Product Warranty	5 Years	Battery Warranty	1 Year
Net Weight	0.6 kg		

TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50-60Hz
Class Protection	2	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	40,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Polycarbonate
Dimensions - Height	70 mm	Dimensions - Width	110 mm
Dimensions - Depth	355 mm	IP Rating	IP65

PRODUCT INFORMATION

Wattage Combined	4W	CCT Combined	6400K
Luminaire Lumens Combined	270 lm	lm/W Combined	68 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.8
Emergency Lumen Output	270 lm	Lighting Technology used	LED





Non-Directional or Directional	NDLS	Mains or non-mains	MLS
Connected light source (CLS)	FALSE	Colour tuneable light source	FALSE
High Luminance light source	FALSE	Anti Glare shield	FALSE
Dimmable	Not Dimmable	Correlated Colour temperature type	SINGLE_VALUE
Correlated Colour temperature (K) 1	6,000	Chromaticity coordinates x	0.3
Chromaticity coordinates y	0.33	Peak Luminous Intensity (cd)	40
Stroboscopic effect metric (SVM)	0.012	Flicker Metric (pst)	0.1
R9 colour rendering index	13	Survival factor @6000hrs	0.9
Spectrum report available	Yes	Displacement Factor	0.91
CCT1/WATT1: Rated Peak Intensity	40 cd		





IP65

PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
VECOMEM3	Emergency, Without Legend	4 W	6400 K	270 lm	68 lm/W
VECOMEM3L	Emergency, With Adhesive Legends	4 W	6400 K	270 lm	68 lm/W

ACCESSORIES

Product Code	Description	MOM / OPQ
EB21	Ni-Cd 3.6V 800mAh Battery	1 / 100
VECOEMISOL	ISO Legend Set for Economy Emergency Bulkhead	1 / 500
BFRAME	Semi-Recessed Emergency Bulkhead Frame	1 / 50
ISOLGDSET	ISO Legend Set for Emergency Bulkheads	1 / 12
LGDSET	Legend Set For EM Bulkhead	1 / 12

PACKAGING

Packaging Type	Plain Box
Individual unit gross weight	565 g
Pallet Layer Qty	60
Pallet Layers	5
Pallet Qty	300
MOM / OPQ	1 / 10

