




VECOMEM3L

Maintained IP65 Emergency rectangular bulkhead 4W LED 6400K with ISO 7010 legend

FEATURES

- Polycarbonate construction
- Hinged gear tray & push fit terminals
- 20mm gland entries as standard
- Facility for remote switching and non-maintained mode
- 270 lm when connected to mains, 130 lm when connected to battery
- 20m viewing distance
- Minimum 3 hour functionality in emergency mode
- Ni-Cd 3.6V 800mAh battery 1 year warranty - Replacement battery code: EB21



GENERAL INFORMATION

| | | | |
|------------------|-------------------|------------------|-------------------|
| Light Source | LED | Colour / Finish | White |
| Application | Internal/External | Mounting Type | Surface, Recessed |
| Product Warranty | 5 Years | Battery Warranty | 1 Year |
| Net Weight | 0.6 kg | | |

TECHNICAL INFORMATION

| | | | |
|-----------------------------|--------|-------------------------------|---------------|
| Nominal Voltage | 240 | Frequency | 50-60Hz |
| Class Protection | 2 | Operating Temperature (Min) | -25 °C |
| Operating Temperature (Max) | 45 °C | Average Rated Life | 40,000 h |
| Number of switching cycles | 15,000 | Construction Materials Line 1 | Polycarbonate |
| Dimensions - Height | 70 mm | Dimensions - Width | 355 mm |
| Dimensions - Depth | 110 mm | IP Rating | IP65 |

PRODUCT INFORMATION

| | | | |
|---------------------------|--------|--------------------------|---------|
| Wattage Combined | 4W | CCT Combined | 6400K |
| Luminaire Lumens Combined | 270 lm | lm/W Combined | 68 lm/w |
| Beam Angle | 120° | CRI | 80 |
| SDCM | <6 | Lumen Maintenance | 0.8 |
| Emergency Lumen Output | 130 lm | Lighting Technology used | LED |





| | | | |
|----------------------------------|--------------|------------------------------------|--------------|
| Non-Directional or Directional | NDLS | Mains or non-mains | MLS |
| Connected light source (CLS) | FALSE | Colour tuneable light source | FALSE |
| High Luminance light source | FALSE | Anti Glare shield | FALSE |
| Dimmable | Not Dimmable | Correlated Colour temperature type | SINGLE_VALUE |
| Chromaticity coordinates x | 0.3 | Chromaticity coordinates y | 0.33 |
| Stroboscopic effect metric (SVM) | 0.0 | Flicker Metric (pst) | 0.1 |
| R9 colour rendering index | 13.0 | Survival factor @6000hrs | 0.9 |
| Claim LED Replace Fluorescent | FALSE | Spectrum report available | Yes |
| Displacement Factor | 0 | CCT1/WATT1: Rated Peak Intensity | 40 cd |





| PHOTOMETRICS | | | | | |
|--------------|----------------------------------|-------|--------|------------------|---------|
| Product Code | Product Type | Watts | CCT | Luminaire lumens | Lm/W |
| VECOMEM3 | Emergency, Without Legend | 4 W | 6400 K | 270 lm | 68 lm/W |
| VECOMEM3L | Emergency, With Adhesive Legends | 4 W | 6400 K | 270 lm | 68 lm/W |

| ACCESSORIES | | |
|--------------|---|-----------|
| Product Code | Description | MOM / OPQ |
| EB21 | Ni-Cd 3.6V 800mAh Battery | 1 / 100 |
| BFRAME | Semi-Recessed Emergency Bulkhead Frame | 1 / 50 |
| VECOEMISOL | ISO Legend Set for Economy Emergency Bulkhead | 1 / 500 |
| ISOLGDSET | ISO Legend Set for Emergency Bulkheads | 1 / 12 |
| LGDSET | Legend Set For EM Bulkhead | 1 / 12 |

| PACKAGING | |
|------------------------------|-----------|
| Packaging Type | Plain Box |
| Individual unit gross weight | 581 g |
| Pallet Layer Qty | 60 |
| Pallet Layers | 5 |
| Pallet Qty | 300 |
| MOM / OPQ | 1 / 10 |

