Spec Sheet VECOPANBL










DESCRIPTION

This commercial backlit LED panel produces a uniform light output with easy loop-in, loop-out push fit connectors whilst maintaining an ultra thin 35mm depth

FEATURES

- Zero maintenance, integral light source providing instant light output. Ra: ≥80, high CRI to minimise colour distortion of illuminated products in retail applications
- Operating temperature: 5 to 45°C
- Lumen efficacy: 96 lm/W
- Includes a plug and play constant current non-dimmable LED driver. Push fit wiring terminal direct into the LED driver
- · Can be recessed in the ceiling or suspended from wires. Surface mounting can be achieved through the mounting box available separately. Emergency battery packs also available
- · Back lit: offering a bright neutral white lighting effect
- White trim finish to match the majority of T. bar ceilings





GENERAL INFORMATION			
Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Recessed
Product Warranty	5 Years	Net Weight	1.83 kg
Energy Efficiency Class	F		

TECHNICAL INFORMATION			
Nominal Voltage	240 V	Frequency	50Hz
Class Protection	2	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	30,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Steel
Construction Materials Line 2	Polystyrene	Dimensions - Height	35 mm
Dimensions - Width	595 mm	Dimensions - Depth	595 mm

PRODUCT INFORMATION			
Wattage Combined	36W	CCT Combined	4000K
Luminaire Lumens Combined	3450 lm	lm/W Combined	96 lm/w
Beam Angle	110°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
IP Rating	IP20		
















P20

ACCESSORIES		
Product Code	Description	MOM / OPQ
PANSUSKIT	Suspension Pack for Panels	1 / 100
SURFACEMK	Screwless Surface Mount Kit	1 / 20
SUSPACK	Suspension Pack for LED Slim Panel Lights	1 / 300
ЕВРМЗ	Emergency Battery Pack	1 / 10
EBPM3LI	Li-lon Battery Pack	1 / 40
SEEBPM3	Self-Test Emergency Battery Pack	1 / 10

PACKAGING		
Packaging Type	Plain Box	
Individual unit gross weight	2,178 g	
Pallet Qty	0	
MOM / OPQ	1/6	

(E





