



VECORCFL10


Rechargeable floodlight IP44 10W LED 4000K

DESCRIPTION

The portable rechargeable floodlights come in a 10W and 20W output with a fully adjustable bracket for flexibility in a number of internal and external applications. Complete with a mains charger and car charger the floodlights provide consistent light output for upto 4 hours on one charge

FEATURES

- ABS housing & safety glass cover
- 4 hours illumination (with full charge)
- Charge times from full discharge are as follows: 6 hours (mains charger) / 6 hours (car charger)
- IP44: enables internal and external use
- Mains charger and car charger Included
- 10W: 2 x 18650 Li-ion battery - 3.7V, capacity 2200mAh



GENERAL INFORMATION

Light Source	LED	Colour / Finish	Yellow
Application	Internal/External	Product Warranty	5 Years
Battery Warranty	5 Years	Net Weight	0.58 kg

TECHNICAL INFORMATION

Nominal Voltage	3.7 V	Frequency	50-60Hz
Operating Temperature (Min)	25 °C	Operating Temperature (Max)	40 °C
Average Rated Life	30,000 h	Number of switching cycles	15,000
Construction Materials Line 1	ABS	Dimensions - Height	56 mm
Dimensions - Width	114 mm	Dimensions - Depth	165 mm

PRODUCT INFORMATION

Wattage Combined	10W	CCT Combined	4000K
Luminaire Lumens Combined	650 lm	lm/W Combined	65 lm/w
Beam Angle	120°	CRI	70
SDCM	<6	Lumen Maintenance	0.8
IP Rating	IP44		





IP44

PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
VECORCFL10	Standard	10 W	4000 K	650 lm	65 lm/W
VECORCFL20	Standard	20 W	4000 K	1300 lm	65 lm/W

PACKAGING

Packaging Type	Colour Box
Individual unit gross weight	666 g
Intermediate Carton Depth (mm)	210 mm
Intermediate Carton Width (mm)	315 mm
Intermediate Carton Height (mm)	290 mm
Intermediate Pack Qty.	10
Pallet Layer Qty	140
Pallet Layers	4
Pallet Qty	560
MOM / OPQ	1 / 10

