## **Spec Sheet VECOTWINSP**









## DESCRIPTION

Reduced battery capacity requirement allows a more compact design reducing the weight dramatically compared to traditional products facilitating easier installation, an ideal choice for internal applications requiring practical emergency lighting

## **FEATURES**

- Horizontally and vertically adjustable heads, with 180° rotation across the horizontal plane
- · Individual indicator to show 'Lamps Healthy' and 'Charge'
- · Minimum 3 hour functionality in emergency mode
- Battery: Ni-Cd 3.6V 4Ah. Battery 1 year warranty Replacement battery code: EB13
- Polycarbonate construction
- · Push fit terminals



50mm



TECHNICAL INFORMATION				
Nominal Voltage	240 V	Frequency	50-60Hz	
Class Protection	2	Operating Temperature (Min)	-20 °C	
Operating Temperature (Max)	45 °C	Average Rated Life	40,000 h	
Number of switching cycles	20,000	Construction Materials Line 1	Polycarbonate	
Dimensions - Height	285 mm	Dimensions - Width	250 mm	
Dimensions - Depth	50 mm			

PRODUCT INFORMATION					
Wattage Combined	2W	CCT Combined	6200K		
Luminaire Lumens Combined	435 lm	lm/W Combined	218 lm/w		
Beam Angle	120°	CRI	80		
SDCM	<6	IP Rating	IP20		
Emergency Lumen Output	435 lm				
















P20

ACCESSORIES		
Product Code	Description	MOM / OPQ
EB13	Ni-Cd 3.6V 4000mAh Side-by-side Battery	1/1

PACKAGING		
Packaging Type	Plain Box	
Individual unit gross weight	1,015 g	
Pallet Layer Qty	120	
Pallet Layers	3	
Pallet Qty	360	
MOM / OPQ	1 / 20	







