



Compact Emergency LED Twinspot

Compact white twinspot 2 x 2W LED 6300K



DESCRIPTION

Reduced battery capacity requirement allows a more compact design reducing the weight dramatically compared to traditional products facilitating easier installation, an ideal choice for internal applications requiring practical emergency lighting

FEATURES

- Horizontally and vertically adjustable heads, with 180° rotation across the horizontal plane
- Individual indicator to show 'Lamps Healthy' and 'Charge'
- Minimum 3 hour functionality in emergency mode
- Battery: Ni-Cd 3.6V 4Ah. Battery 1 year warranty - Replacement battery code: EB13
- Polycarbonate construction
- Push fit terminals

GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Battery Warranty	1 Year
Net Weight	0.7 kg		

TECHNICAL INFORMATION

Nominal Voltage	240 V	Frequency	50-60Hz
Class Protection	2	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	40,000 h
Number of switching cycles	20,000	Construction Materials Line 1	Polycarbonate
Dimensions - Height	285 mm	Dimensions - Width	250 mm
Dimensions - Depth	50 mm	IP Rating	IP20

PRODUCT INFORMATION

Wattage Combined	2W	CCT Combined	6200K
Luminaire Lumens Combined	435 lm	lm/W Combined	218 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Emergency Lumen Output	435 lm
Dimmable	Not Dimmable	CCT1/WATT1: Rated Peak Intensity	100 cd



ISO 9001



UKAS



ISO 14001



OHSAS 18001





PHOTOMETRICS					
Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
VECOTWINSP	Emergency	2 W	6200 K	435 lm	218 lm/W
SETSPOT	Emergency	4.5 W	6000 K	437 lm	97 lm/W

ACCESSORIES

Product Code	Description	MOM / OPQ
EB13	Ni-Cd 3.6V 4000mAh Side-by-side Battery	1 / 1

PACKAGING

Packaging Type	Plain Box
Individual unit gross weight	1,015 g
Pallet Layer Qty	120
Pallet Layers	3
Pallet Qty	360
MOM / OPQ	1 / 20

