



VECO


5ft 45W 4000K LED Economy Weatherproof

DESCRIPTION

Low profile IP65 batten which is half the height of a typical weatherproof, the batten offers a slim design to suit certain applications. Pre wired with a 1.5m flex makes installation quick and simple

FEATURES

- Polycarbonate construction
- Pre-wired with 1.5m cable



GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal/External	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	0.02 kg
Energy Efficiency Class	F		

TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50-60Hz
Class Protection	2	Average Rated Life	30,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Polycarbonate
Dimensions - Height	35 mm	Dimensions - Width	52 mm
Dimensions - Depth	1500 mm	IP Rating	IP65

PRODUCT INFORMATION

Wattage Combined	45W	CCT Combined	4000K
Luminaire Lumens Combined	4400 lm	lm/W Combined	98 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.8
Lighting Technology used	LED	Non-Directional or Directional	NDLS
Mains or non-mains	MLS	Connected light source (CLS)	FALSE





Colour tuneable light source	FALSE	High Luminance light source	FALSE
Anti Glare shield	FALSE	Dimmable	Not Dimmable
Correlated Colour temperature type	SINGLE_VALUE	Correlated Colour temperature (K) 1	4,000
Chromaticity coordinates x	0.379	Chromaticity coordinates y	0.377
Peak Luminous Intensity (cd)	420 cd	Stroboscopic effect metric (SVM)	0.1
Flicker Metric (pst)	0.1	R9 colour rendering index	7.0
Survival factor @6000hrs	0.9	Claim LED Replace Fluorescent	FALSE
Spectrum report available	Yes	Displacement Factor	0.9
CCTI/WATTI: Rated Peak Intensity	420 cd		





IP65

PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
VECOWP5FT	Standard	45	4000 K	4400 lm	98 lm/W

PACKAGING

Packaging Type	Plain Box
Individual unit gross weight	656 g
Pallet Layer Qty	80
Pallet Layers	5
Pallet Qty	400
MOM / OPQ	1 / 20

