
Spec Sheet WELLBKPIR

eterna.

5 Year Warranty

IP65





LED Well Glass

Black polycarbonate well glass 10W LED 4000K IP65 with 120° PIR

DESCRIPTION

Flexible and decorative range of fittings ideally suited for outdoor applications requiring corner lights

FEATURES

- Polycarbonate construction in white or black finish with opal polycarbonate diffuser
- Complete solution for flat wall or corner mounting Bracket included for optional corner mounting
- Factory preset 120° PIR
- 10 lux 7 minutes duration with no override facility

GENERAL INFORMATION			
Light Source	LED	**Colour / Finish**	Black
Application	External	**Mounting Type**	Surface
Product Warranty	5 Years	**Net Weight**	0.35 kg
Energy Efficiency Class	F		

TECHNICAL INFORMATION			
Nominal Voltage	240	**Frequency**	50Hz
Class Protection	2	**Operating Temperature (Min)**	-20 °C
Operating Temperature (Max)	45 °C	**Average Rated Life**	25,000 h
Number of switching cycles	12,500	**Construction Materials Line 1**	Polycarbonate
Dimensions - Height	197 mm	**Dimensions - Width**	122 mm
Dimensions - Depth	214 mm	**IP Rating**	IP65

PRODUCT INFORMATION			
Wattage Combined	10W	**CCT Combined**	4000K
Luminaire Lumens Combined	818 lm	**lm/W Combined**	82 lm/w
Beam Angle	120°	**CRI**	80
SDCM	<6	**Lumen Maintenance**	0.7
Displacement Factor	0.93	**CCT1/WATT1: Rated Peak Intensity**	241 cd

CE

UK CA

Member of theLIA

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

PHOTOMETRICS					
Product Code	**Product Type**	**Watts**	**CCT**	**Luminaire lumens**	**Lm/W**
WELLBKPIR	PIR	10 W	4000 K	818 lm	82 lm/W
WELLBKSTD	Standard	10 W	4000 K	818 lm	82 lm/W
WELLWHPIR	PIR	10 W	4000 K	818 lm	82 lm/W
WELLWHSTD	Standard	10 W	4000 K	818 lm	82 lm/W

PACKAGING	
Packaging Type	Colour Box
Individual unit gross weight	457 g
Pallet Layer Qty	96
Pallet Layers	3
Pallet Qty	288
MOM / OPQ	1 / 8