Spec Sheet WELLWHPIR

5 Year Warranty

IP65



Well Glass

White polycarbonate well glass 10W LED 4000K IP65 with PIR

DESCRIPTION

Flexible and decorative range of fittings ideally suited for outdoor applications requiring corner lights

FEATURES

- Polycarbonate construction in white or black finish with opal polycarbonate diffuser
- Complete solution for flat wall or corner mounting Bracket included for optional corner mounting
- On Off factory preset 120° PIR
- 10 lux 7 minute duration with no override facility



GENERAL INFORMATION			
Light Source	LED	**Colour / Finish**	White
Application	External	**Mounting Type**	Surface
Product Warranty	5 Years	**Net Weight**	0.37 kg
Energy Efficiency Class	F		

TECHNICAL INFORMATION			
Nominal Voltage	240	**Frequency**	50Hz
Class Protection	2	**Operating Temperature (Min)**	-20 °C
Operating Temperature (Max)	45 °C	**Average Rated Life**	25,000 h
Number of switching cycles	12,500	**Construction Materials Line 1**	Polycarbonate
Dimensions - Height	197 mm	**Dimensions - Width**	122 mm
Dimensions - Depth	214 mm	**IP Rating**	IP65

PRODUCT INFORMATION			
Wattage Combined	10W	**CCT Combined**	4000K
Luminaire Lumens Combined	818 lm	**lm/W Combined**	82 lm/w
Beam Angle	120°	**CRI**	80
SDCM	<6	**Lumen Maintenance**	0.7
Displacement Factor	0.93	**CCT1/WATT1: Rated Peak Intensity**	241 cd

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

PHOTOMETRICS					
Product Code	**Product Type**	**Watts**	**CCT**	**Luminaire lumens**	**Lm/W**
WELLBKPIR	PIR	10 W	4000 K	818 lm	82 lm/W
WELLBKSTD	Standard	10 W	4000 K	818 lm	82 lm/W
WELLWHPIR	PIR	10 W	4000 K	818 lm	82 lm/W
WELLWHSTD	Standard	10 W	4000 K	818 lm	82 lm/W

PACKAGING	
Packaging Type	Colour Box
Individual unit gross weight	468 g
Pallet Layer Qty	96
Pallet Layers	3
Pallet Qty	288
MOM / OPQ	1 / 8