



## Well Glass


White polycarbonate well glass 10W LED  
4000K IP65 with PIR

### DESCRIPTION

Flexible and decorative range of fittings ideally suited for outdoor applications requiring corner lights

### FEATURES

- Polycarbonate construction in white or black finish with opal polycarbonate diffuser
- Complete solution for flat wall or corner mounting Bracket included for optional corner mounting
- On Off factory preset 120° PIR
- 10 lux 7 minute duration with no override facility



### GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	External	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	0.37 kg
Energy Efficiency Class	F		

### TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50Hz
Class Protection	2	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	25,000 h
Number of switching cycles	12,500	Construction Materials Line 1	Polycarbonate
Dimensions - Height	197 mm	Dimensions - Width	122 mm
Dimensions - Depth	214 mm	IP Rating	IP65

### PRODUCT INFORMATION

Wattage Combined	10W	CCT Combined	4000K
Luminaire Lumens Combined	818 lm	lm/W Combined	82 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
Displacement Factor	0.93	CCT1/WATT1: Rated Peak Intensity	241 cd





IP65

PHOTOMETRICS					
Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
WELLBKPIR	PIR	10 W	4000 K	818 lm	82 lm/W
WELLBKSTD	Standard	10 W	4000 K	818 lm	82 lm/W
WELLWHPIR	PIR	10 W	4000 K	818 lm	82 lm/W
WELLWHSTD	Standard	10 W	4000 K	818 lm	82 lm/W

PACKAGING	
Packaging Type	Colour Box
Individual unit gross weight	468 g
Pallet Layer Qty	96
Pallet Layers	3
Pallet Qty	288
MOM / OPQ	1 / 8

