Spec Sheet WP42

eterna.

5 Year Warranty

IP65

IK10



4FT Twin LED Weatherproof Fitting


4ft 38W 4000K Twin LED Weatherproof Fitting

DESCRIPTION

This range is quick and easy to install due to "loop in & out" push fit connectors and features an IK10 "anti-drop" diffuser. Available in both single and twin fixtures with 6 output versions in each length, options include integral emergency and on / off microwave sensor

FEATURES

- Multiple cable entries, allowing for "loop in & out" wiring via push fit terminal block
- "Anti-drop" polycarbonate diffuser & gear tray
- Three mounting options - BESA box, directly onto ceiling surfaces or stainless steel suspension clips (included)
- Supplied with a 20mm IP65 gland & fixings kit
- IK10 rated fitting
- Producing up to 106 lm / W



GENERAL INFORMATION			
Light Source	LED	**Colour / Finish**	Grey
Application	Internal/External	**Mounting Type**	Surface, Suspended
Product Warranty	5 Years	**Net Weight**	2 kg
Energy Efficiency Class	E		

TECHNICAL INFORMATION			
Nominal Voltage	240	**Frequency**	50Hz
Class Protection	1	**Average Rated Life**	40,000 h
Number of switching cycles	15,000	**Construction Materials Line 1**	ABS
Construction Materials Line 2	PC	**Dimensions - Height**	82 mm
Dimensions - Width	135 mm	**Dimensions - Depth**	1260 mm
IK Rating	IK10	**IP Rating**	IP65

PRODUCT INFORMATION			
Wattage Combined	38W	**CCT Combined**	4000K
Luminaire Lumens Combined	3880 lm	**lm/W Combined**	102 lm/w
Beam Angle	120°	**CRI**	80
SDCM	<6	**Lumen Maintenance**	0.7
Lighting Technology used	LED	**Non-Directional or Directional**	NDLS

CE

UK CA

Member of theLIA

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

Spec Sheet WP42

Mains or non-mains	MLS	**Connected light source (CLS)**	FALSE
Colour tuneable light source	FALSE	**High Luminance light source**	FALSE
Anti Glare shield	FALSE	**Dimmable**	Not Dimmable
CCT1/WATT1: Rated Peak Intensity	880 cd		

5 Year Warranty

IP65

IK10

eterna.

5 Year Warranty

IP65

IK10

PHOTOMETRICS					
Product Code	**Product Type**	**Watts**	**CCT**	**Luminaire lumens**	**Lm/W**
WP41	Standard	19 W	4000 K	1950 lm	103 lm/W
WP41EM3	Emergency	19 W	4000 K	1950 lm	103 lm/W
WP42	Standard	38 W	4000 K	3880 lm	102 lm/W
WP42MW	On / Off Microwave	38 W	4000 K	3880 lm	102 lm/W
WP51EM3	Emergency	30 W	4000 K	3180 lm	106 lm/W
WP51MW	On / Off Microwave	30 W	4000 K	3180 lm	106 lm/W
WP51MW3	Emergency, On / Off Microwave	30 W	4000 K	3180 lm	106 lm/W
WP52	Standard	58 W	4000 K	6020 lm	104 lm/W
WP52EM3	Emergency	58 W	4000 K	6020 lm	104 lm/W
WP52MW	On / Off Microwave	58 W	4000 K	6020 lm	104 lm/W
WP61	Standard	35 W	4000 K	3680 lm	105 lm/W
WP61EM3	Emergency	35 W	4000 K	3680 lm	105 lm/W
WP61MW	On / Off Microwave	35 W	4000 K	3680 lm	105 lm/W
WP62	Standard	68 W	4000 K	6980 lm	103 lm/W
WP62EM3	Emergency	68 W	4000 K	6980 lm	103 lm/W
WP62MW	On / Off Microwave	68 W	4000 K	6980 lm	103 lm/W
WP42EM3	Emergency	38 W	4000 K	3880 lm	102 lm/W
WP41MW3	Emergency, On / Off Microwave	19 W	4000 K	1950 lm	103 lm/W
WP42MW3	Emergency, On / Off Microwave	38 W	4000 K	3880 lm	102 lm/W
WP52MW3	Emergency, On / Off Microwave	58 W	4000 K	6020 lm	104 lm/W
WP61MW3	Emergency, On / Off Microwave	35 W	4000 K	3680 lm	105 lm/W

PACKAGING	
Packaging Type	Plain Box
Individual unit gross weight	2,012 g
Pallet Layer Qty	18
Pallet Layers	4
Pallet Qty	72
MOM / OPQ	1 / 6

CE

UK CA

Member of theLIA