



## 6FT Twin LED Weatherproof Fitting


6ft 68W 4000K Twin LED Weatherproof Fitting

### DESCRIPTION

This range is quick and easy to install due to “loop in & out” push fit connectors and features an IK10 “anti-drop” diffuser. Available in both single and twin fixtures with 6 output versions in each length, options include integral emergency and on / off microwave sensor

### FEATURES

- Multiple cable entries, allowing for “loop in & out” wiring via push fit terminal block
- “Anti-drop” polycarbonate diffuser & gear tray for ease of installation
- Three mounting options - BESA box, directly onto ceiling surfaces or stainless steel suspension clips (included)
- Supplied with a 20mm IP65 gland & fixings kit
- IK10 rated fitting
- Producing up to 106 lm / W



### GENERAL INFORMATION

Light Source	LED	Colour / Finish	Grey
Application	Internal/External	Mounting Type	Surface, Suspended
Product Warranty	5 Years	Net Weight	2.5 kg
Energy Efficiency Class	E		

### TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50Hz
Class Protection	1	Average Rated Life	40,000 h
Number of switching cycles	15,000	Construction Materials Line 1	ABS
Construction Materials Line 2	PC	Dimensions - Height	82 mm
Dimensions - Width	135 mm	Dimensions - Depth	1830 mm
IK Rating	IK10	IP Rating	IP65

### PRODUCT INFORMATION

Wattage Combined	68W	CCT Combined	4000K
Luminaire Lumens Combined	6980 lm	lm/W Combined	103 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
Lighting Technology used	LED	Non-Directional or Directional	NDLS



Mains or non-mains	MLS	Connected light source (CLS)	FALSE
Colour tuneable light source	FALSE	High Luminance light source	FALSE
Anti Glare shield	FALSE	Dimmable	Not Dimmable
CCT1/WATT1: Rated Peak Intensity	1,610 cd		



IP65



IK10





IP65



IK10

## PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
WP41	Standard	19	4000 K	1950 lm	103 lm/W
WP41EM3	Emergency	19	4000 K	1950 lm	103 lm/W
WP42	Standard	38	4000 K	3880 lm	102 lm/W
WP42MW	On / Off Microwave	38	4000 K	3880 lm	102 lm/W
WP51EM3	Emergency	30	4000 K	3180 lm	106 lm/W
WP51MW	On / Off Microwave	30	4000 K	3180 lm	106 lm/W
WP51MW3	Emergency, On / Off Microwave	30	4000 K	3180 lm	106 lm/W
WP52	Standard	58	4000 K	6020 lm	104 lm/W
WP52EM3	Emergency	58	4000 K	6020 lm	104 lm/W
WP52MW	On / Off Microwave	58	4000 K	6020 lm	104 lm/W
WP61	Standard	35	4000 K	3680 lm	105 lm/W
WP61EM3	Emergency	35	4000 K	3680 lm	105 lm/W
WP61MW	On / Off Microwave	35	4000 K	3680 lm	105 lm/W
WP62	Standard	68	4000 K	6980 lm	103 lm/W
WP62EM3	Emergency	68	4000 K	6980 lm	103 lm/W
WP62MW	On / Off Microwave	68	4000 K	6980 lm	103 lm/W
WP42EM3	Emergency	38	4000 K	3880 lm	102 lm/W
WP41MW3	Emergency, On / Off Microwave	19	4000 K	1950 lm	103 lm/W
WP42MW3	Emergency, On / Off Microwave	38	4000 K	3880 lm	102 lm/W
WP52MW3	Emergency, On / Off Microwave	58	4000 K	6020 lm	104 lm/W
WP61MW3	Emergency, On / Off Microwave	35	4000 K	3680 lm	105 lm/W

## PACKAGING

Packaging Type	Plain Box
Individual unit gross weight	2,971 g
Pallet Layer Qty	18
Pallet Layers	6
Pallet Qty	108
MOM / OPQ	1 / 6

