









6ft 68W 4000K Twin Emergency LED Weatherproof Fitting with MW


DESCRIPTION

This range is quick and easy to install due to "loop in & out" push fit connectors and features an IK10 "anti-drop" diffuser. Available in both single and twin fixtures with 6 output versions in each length, options include integral emergency and on / off microwave sensor

FEATURES

- Multiple cable entries, allowing for "loop in & out" wiring via push fit terminal block
- "Anti-drop" polycarbonate diffuser & gear tray
- Three mounting options BESA box, directly onto ceiling surfaces or stainless steel suspension clips (included)
- Supplied with a 20mm IP65 gland & fixings kit
- IK10 rated fitting
- Producing up to 106 lm / W
- Emergency 3 hour duration maintained operation with the facility for remote switching
- Integral adjustable microwave sensor





GENERAL INFORMATION				
Light Source	LED	Colour / Finish	Grey	
Application	Internal/External	Mounting Type	Surface, Suspended	
Product Warranty	5 Years	Battery Warranty	1 Year	
Net Weight	2.80 kg	Energy Efficiency Class	E	

TECHNICAL INFORMATION				
Nominal Voltage	240 V	Frequency	50Hz	
Class Protection	1	Average Rated Life	40,000 h	
Number of switching cycles	15,000	Construction Materials Line 1	ABS	
Construction Materials Line 2	PC	Dimensions - Height	82 mm	
Dimensions - Width	135 mm	Dimensions - Depth	1830 mm	

PRODUCT INFORMATION			
Wattage Combined	68W	CCT Combined	4000K
Luminaire Lumens Combined	6980 lm	lm/W Combined	103 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
IP Rating	IP65	IK Rating	IK10
















P65	





PACKAGING	
Packaging Type	Plain Box
Individual unit gross weight	3,314 g
Pallet Qty	0
MOM / OPQ	0 / 0







