



6FT Twin LED Weatherproof Fitting


6ft 68W 4000K Twin Emergency LED Weatherproof Fitting with MW

DESCRIPTION

This range is quick and easy to install due to "loop in & out" push fit connectors and features an IK10 "anti-drop" diffuser. Available in both single and twin fixtures with 6 output versions in each length, options include integral emergency and on / off microwave sensor

FEATURES

- Multiple cable entries, allowing for "loop in & out" wiring via push fit terminal block
- "Anti-drop" polycarbonate diffuser & gear tray
- Three mounting options - BESA box, directly onto ceiling surfaces or stainless steel suspension clips (included)
- Supplied with a 20mm IP65 gland & fixings kit
- IK10 rated fitting
- Producing up to 106 lm / W
- Emergency 3 hour duration maintained operation with the facility for remote switching
- Integral adjustable microwave sensor



GENERAL INFORMATION

Light Source	LED	Colour / Finish	Grey
Application	Internal/External	Mounting Type	Surface, Suspended
Product Warranty	5 Years	Battery Warranty	1 Year
Net Weight	2.80 kg	Energy Efficiency Class	E

TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50Hz
Class Protection	1	Average Rated Life	40,000 h
Number of switching cycles	15,000	Construction Materials Line 1	ABS
Construction Materials Line 2	PC	Dimensions - Height	82 mm
Dimensions - Width	135 mm	Dimensions - Depth	1830 mm
IK Rating	IK10	IP Rating	IP65

PRODUCT INFORMATION

Wattage Combined	68W	CCT Combined	4000K
Luminaire Lumens Combined	6980 lm	lm/W Combined	103 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
Emergency Lumen Output	330 lm	Lighting Technology used	LED



Non-Directional or Directional	NDLS	Mains or non-mains	MLS
Connected light source (CLS)	FALSE	Colour tuneable light source	FALSE
High Luminance light source	FALSE	Anti Glare shield	FALSE
Dimmable	Not Dimmable	CCTI/WATTI: Rated Peak Intensity	1,610 cd



IP65



IK10



PHOTOMETRICS					
Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
WP62MW3	Emergency, On / Off Microwave	68	4000 K	6980 lm	103 lm/W



ACCESSORIES		
Product Code	Description	MOM / OPQ
EB20	Li-Ion 6.4V 1500mAh Stick Battery	1 / 100

PACKAGING	
Packaging Type	Plain Box
Individual unit gross weight	3,314 g
Pallet Layer Qty	18
Pallet Layers	4
Pallet Qty	72
MOM / OPQ	1 / 0

