



6FT Twin LED Weatherproof Fitting


6ft 68W 4000K Twin LED Weatherproof Fitting with MW

DESCRIPTION

This range is quick and easy to install due to "loop in & out" push fit connectors and features an IK10 "anti-drop" diffuser. Available in both single and twin fixtures with 6 output versions in each length, options include integral emergency and on / off microwave sensor

FEATURES

- Multiple cable entries, allowing for "loop in & out" wiring via push fit terminal block
- "Anti-drop" polycarbonate diffuser & gear tray
- Three mounting options - BESA box, directly onto ceiling surfaces or stainless steel suspension clips (included)
- Supplied with a 20mm IP65 gland & fixings kit
- IK10 rated fitting
- Producing up to 106 lm / W
- Integral adjustable microwave sensor



GENERAL INFORMATION

| | | | |
|-------------------------|-------------------|-----------------|--------------------|
| Light Source | LED | Colour / Finish | Grey |
| Application | Internal/External | Mounting Type | Surface, Suspended |
| Product Warranty | 5 Years | Net Weight | 0 kg |
| Energy Efficiency Class | E | | |

TECHNICAL INFORMATION

| | | | |
|-------------------------------|--------|-------------------------------|----------|
| Nominal Voltage | 240 | Frequency | 50Hz |
| Class Protection | 1 | Average Rated Life | 40,000 h |
| Number of switching cycles | 15,000 | Construction Materials Line 1 | ABS |
| Construction Materials Line 2 | PC | Dimensions - Height | 82 mm |
| Dimensions - Width | 135 mm | Dimensions - Depth | 1830 mm |
| IK Rating | IK10 | IP Rating | IP65 |

PRODUCT INFORMATION

| | | | |
|---------------------------|---------|--------------------------------|----------|
| Wattage Combined | 68W | CCT Combined | 4000K |
| Luminaire Lumens Combined | 6980 lm | lm/W Combined | 103 lm/w |
| Beam Angle | 120° | CRI | 80 |
| SDCM | <6 | Lumen Maintenance | 0.7 |
| Lighting Technology used | LED | Non-Directional or Directional | NDLS |



| | | | |
|----------------------------------|----------|------------------------------|--------------|
| Mains or non-mains | MLS | Connected light source (CLS) | FALSE |
| Colour tuneable light source | FALSE | High Luminance light source | FALSE |
| Anti Glare shield | FALSE | Dimmable | Not Dimmable |
| CCT1/WATT1: Rated Peak Intensity | 1,610 cd | | |



IP65



IK10





IP65



IK10

PHOTOMETRICS

| Product Code | Product Type | Watts | CCT | Luminaire lumens | Lm/W |
|--------------|-------------------------------|-------|--------|------------------|----------|
| WP41 | Standard | 19 W | 4000 K | 1950 lm | 103 lm/W |
| WP41EM3 | Emergency | 19 W | 4000 K | 1950 lm | 103 lm/W |
| WP42 | Standard | 38 W | 4000 K | 3880 lm | 102 lm/W |
| WP42MW | On / Off Microwave | 38 W | 4000 K | 3880 lm | 102 lm/W |
| WP51EM3 | Emergency | 30 W | 4000 K | 3180 lm | 106 lm/W |
| WP51MW | On / Off Microwave | 30 W | 4000 K | 3180 lm | 106 lm/W |
| WP51MW3 | Emergency, On / Off Microwave | 30 W | 4000 K | 3180 lm | 106 lm/W |
| WP52 | Standard | 58 W | 4000 K | 6020 lm | 104 lm/W |
| WP52EM3 | Emergency | 58 W | 4000 K | 6020 lm | 104 lm/W |
| WP52MW | On / Off Microwave | 58 W | 4000 K | 6020 lm | 104 lm/W |
| WP61 | Standard | 35 W | 4000 K | 3680 lm | 105 lm/W |
| WP61EM3 | Emergency | 35 W | 4000 K | 3680 lm | 105 lm/W |
| WP61MW | On / Off Microwave | 35 W | 4000 K | 3680 lm | 105 lm/W |
| WP62 | Standard | 68 W | 4000 K | 6980 lm | 103 lm/W |
| WP62EM3 | Emergency | 68 W | 4000 K | 6980 lm | 103 lm/W |
| WP62MW | On / Off Microwave | 68 W | 4000 K | 6980 lm | 103 lm/W |
| WP42EM3 | Emergency | 38 W | 4000 K | 3880 lm | 102 lm/W |
| WP41MW3 | Emergency, On / Off Microwave | 19 W | 4000 K | 1950 lm | 103 lm/W |
| WP42MW3 | Emergency, On / Off Microwave | 38 W | 4000 K | 3880 lm | 102 lm/W |
| WP52MW3 | Emergency, On / Off Microwave | 58 W | 4000 K | 6020 lm | 104 lm/W |
| WP61MW3 | Emergency, On / Off Microwave | 35 W | 4000 K | 3680 lm | 105 lm/W |

PACKAGING

| | |
|------------------------------|-----------|
| Packaging Type | Plain Box |
| Individual unit gross weight | 2,763 g |
| Pallet Layer Qty | 18 |
| Pallet Layers | 4 |
| Pallet Qty | 72 |
| MOM / OPQ | 1 / 0 |

