



LED Slim Wall Pack


Wall pack black with opal diffuser 30W
2000lm LED 4200K IP65

DESCRIPTION

Robustly constructed LED integrated wall pack offering 2300 lumens to provide functional pathway lighting and security lighting, an option to have an integrated photocell offers hassle free control enabling dusk to dawn control giving light when required

FEATURES

- Tough polycarbonate housing & captive stainless steel screws
- 20mm knockouts to side and rear
- IP65 IK08 Rated
- Hinged front for easy access



GENERAL INFORMATION

Light Source	LED	Colour / Finish	Black
Application	External	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	1.5 kg
Energy Efficiency Class	F		

TECHNICAL INFORMATION

Nominal Voltage	240 V	Frequency	50Hz
Class Protection	1	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	50,000 h
Number of switching cycles	25,000	Construction Materials Line 1	Polycarbonate
Dimensions - Height	305 mm	Dimensions - Width	206 mm
Dimensions - Depth	120 mm		

PRODUCT INFORMATION

Wattage Combined	30W	CCT Combined	4000K
Luminaire Lumens Combined	2317 lm	lm/W Combined	77 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.8
IP Rating	IP65	IK Rating	IK08





IP65



IK08

PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
WPACKLED	Standard	30 W	4000 K	2317 lm	77 lm/W
WPACKLEDPC	Photocell	30 W	4000 K	2317 lm	77 lm/W

PACKAGING

Packaging Type	Colour Box
Individual unit gross weight	1,965 g
Pallet Layer Qty	24
Pallet Layers	4
Pallet Qty	96
MOM / OPQ	1 / 4

