Spec Sheet WPACKLEDPC


eterna.

5 Year Warranty

IP65

IK08





LED Slim Wall Pack

Wall pack black with opal diffuser 30W 2000lm LED 4200K With Photocell IP65

DESCRIPTION

Robustly constructed LED integrated wall pack offering 2300 lumens to provide functional pathway lighting and security lighting, an option to have an integrated photocell offers hassle free control enabling dusk to dawn control giving light when required

FEATURES

- Tough polycarbonate housing & captive stainless steel screws
- 20mm knockouts to side and rear
- Photocell for dusk to dawn operation
- IP65 IK08 Rated
- Hinged front for easy access

GENERAL INFORMATION			
Light Source	LED	**Colour / Finish**	Black
Application	External	**Mounting Type**	Surface
Product Warranty	5 Years	**Net Weight**	1.5 kg
Energy Efficiency Class	F		

TECHNICAL INFORMATION			
Nominal Voltage	240	**Frequency**	50Hz
Class Protection	I	**Operating Temperature (Min)**	-20 °C
Operating Temperature (Max)	45 °C	**Average Rated Life**	50,000 h
Number of switching cycles	25,000	**Construction Materials Line 1**	Polycarbonate
Dimensions - Height	305 mm	**Dimensions - Width**	206 mm
Dimensions - Depth	120 mm	**IK Rating**	IK08
IP Rating	IP65		

PRODUCT INFORMATION			
Wattage Combined	30W	**CCT Combined**	4000K
Luminaire Lumens Combined	2317 lm	**lm/W Combined**	77 lm/w
Beam Angle	120°	**CRI**	80
SDCM	<6	**Lumen Maintenance**	0.8

CE

UKCA

Member of theLIA

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

Spec Sheet WPACKLEDPC

Lighting Technology used	LED	**Non-Directional or Directional**	NDLS
Mains or non-mains	MLS	**Correlated Colour temperature type**	SINGLE_VALUE
Correlated Colour temperature (K) 1	4,000	**Chromaticity coordinates x**	0.376
Chromaticity coordinates y	0.37	**Peak Luminous Intensity (cd)**	478 cd
Beam Angle range minimum (degrees)	120	**Stroboscopic effect metric (SVM)**	0
Flicker Metric (pst)	0.1	**R9 colour rendering index**	17
Survival factor @6000hrs	0.9	**Spectrum report available**	Yes
Displacement Factor	0.95	**CCT1/WATT1: Rated Peak Intensity**	478 cd

5 Year Warranty

IP65

IK08

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

PHOTOMETRICS					
Product Code	**Product Type**	**Watts**	**CCT**	**Luminaire lumens**	**Lm/W**
WPACKLED	Standard	30 W	4000 K	2317 lm	77 lm/W
WPACKLEDPC	Photocell	30 W	4000 K	2317 lm	77 lm/W

PACKAGING	
Packaging Type	Colour Box
Individual unit gross weight	2,031 g
Pallet Layer Qty	24
Pallet Layers	4
Pallet Qty	96
MOM / OPQ	1 / 4

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D