



LED Slim Wall Pack


Wall pack black with opal diffuser 30W  
2000lm LED 4200K With Photocell IP65

DESCRIPTION

Robustly constructed LED integrated wall pack offering 2300 lumens to provide functional pathway lighting and security lighting, an option to have an integrated photocell offers hassle free control enabling dusk to dawn control giving light when required

FEATURES

- Tough polycarbonate housing & captive stainless steel screws
- 20mm knockouts to side and rear
- Photocell for dusk to dawn operation
- IP65 IK08 Rated
- Hinged front for easy access



GENERAL INFORMATION

|                         |          |                 |         |
|-------------------------|----------|-----------------|---------|
| Light Source            | LED      | Colour / Finish | Black   |
| Application             | External | Mounting Type   | Surface |
| Product Warranty        | 5 Years  | Net Weight      | 1.5 kg  |
| Energy Efficiency Class | F        |                 |         |

TECHNICAL INFORMATION

|                             |        |                               |               |
|-----------------------------|--------|-------------------------------|---------------|
| Nominal Voltage             | 240 V  | Frequency                     | 50Hz          |
| Class Protection            | 1      | Operating Temperature (Min)   | -20 °C        |
| Operating Temperature (Max) | 45 °C  | Average Rated Life            | 50,000 h      |
| Number of switching cycles  | 25,000 | Construction Materials Line 1 | Polycarbonate |
| Dimensions - Height         | 305 mm | Dimensions - Width            | 206 mm        |
| Dimensions - Depth          | 120 mm |                               |               |

PRODUCT INFORMATION

|                           |         |                   |         |
|---------------------------|---------|-------------------|---------|
| Wattage Combined          | 30W     | CCT Combined      | 4000K   |
| Luminaire Lumens Combined | 2317 lm | lm/W Combined     | 77 lm/w |
| Beam Angle                | 120°    | CRI               | 80      |
| SDCM                      | <6      | Lumen Maintenance | 0.8     |
| IP Rating                 | IP65    | IK Rating         | IK08    |





IP65



IK08

#### PHOTOMETRICS

| Product Code | Product Type | Watts | CCT    | Luminaire lumens | Lm/W    |
|--------------|--------------|-------|--------|------------------|---------|
| WPACKLED     | Standard     | 30 W  | 4000 K | 2317 lm          | 77 lm/W |
| WPACKLEDPC   | Photocell    | 30 W  | 4000 K | 2317 lm          | 77 lm/W |

#### PACKAGING

|                              |            |
|------------------------------|------------|
| Packaging Type               | Colour Box |
| Individual unit gross weight | 2,031 g    |
| Pallet Layer Qty             | 24         |
| Pallet Layers                | 4          |
| Pallet Qty                   | 96         |
| MOM / OPQ                    | 1 / 4      |

