



Slim Wallpack




Slim white IP65 wall pack 17W CCT selectable

DESCRIPTION

Slim profile and durable wall pack, available with colour temperature selection to suit different applications. The design offers a contemporary slimmer update to the traditional wall pack available with further energy savings with an option of an integrated photocell

FEATURES

- Colour temperature selectable 3000K, 4000K, 6000K
- Up to 90 lm/W
- ABS base and polycarbonate diffuser
- Slim design
- Opal diffuser, evenly diffused light output
- 20mm cable entries on either side and one to the rear



GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	External	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	0.6 kg
Energy Efficiency Class	E		

TECHNICAL INFORMATION

Nominal Voltage	240 V	Frequency	50Hz
Class Protection	2	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	50,000 h
Number of switching cycles	25,000	Construction Materials Line 1	Polycarbonate
Construction Materials Line 2	ABS	Dimensions - Height	275 mm
Dimensions - Width	185 mm	Dimensions - Depth	70 mm

PRODUCT INFORMATION

Wattage Combined	17W	CCT Combined	3000K / 4000K / 6000K
Luminaire Lumens Combined	1580 - 1595 lm	lm/W Combined	93 - 94 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.8
IP Rating	IP65	IK Rating	IK10



PHOTOMETRICS					
Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
WPCSBK	Standard	17 W	3000 K	1580 lm	93 lm/W
			4000 K	1645 lm	97 lm/W
			6000 K	1595 lm	94 lm/W
WPCSBKPC	Photocell	17 W	3000 K	1580 lm	93 lm/W
			4000 K	1645 lm	97 lm/W
			6000 K	1595 lm	94 lm/W
WPCSWH	Standard	17 W	3000 K	1580 lm	93 lm/W
			4000 K	1645 lm	97 lm/W
			6000 K	1595 lm	94 lm/W
WPCSWHPC	Photocell	17 W	3000 K	1580 lm	93 lm/W
			4000 K	1645 lm	97 lm/W
			6000 K	1595 lm	94 lm/W

PACKAGING	
Packaging Type	Plain Box
Individual unit gross weight	688 g
Pallet Qty	0
MOM / OPQ	1 / 10



IP65



IK10



Colour Temp.
Selectable

