



Slim Wallpack



Slim white IP65 wall pack 17W CCT selectable with photocell

DESCRIPTION

Slim profile and durable wall pack, available with colour temperature selection to suit different applications. The design offers a contemporary slimmer update to the traditional wall pack available with further energy savings with an option of an integrated photocell

FEATURES

- Colour temperature selectable 3000K, 4000K, 6000K
- Up to 90 lm/W
- ABS base and polycarbonate diffuser
- Slim design
- Opal diffuser, evenly diffused light output
- 20mm cable entries on either side and one to the rear
- Photocell for dusk to dawn operation



GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	External	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	0.5 kg
Energy Efficiency Class	E		

TECHNICAL INFORMATION

Nominal Voltage	240 V	Frequency	50Hz
Class Protection	2	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	50,000 h
Number of switching cycles	25,000	Construction Materials Line 1	Polycarbonate
Construction Materials Line 2	ABS	Dimensions - Height	275 mm
Dimensions - Width	185 mm	Dimensions - Depth	70 mm

PRODUCT INFORMATION

Wattage Combined	17W	CCT Combined	3000K / 4000K / 6000K
Luminaire Lumens Combined	1580 - 1595 lm	lm/W Combined	93 - 94 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.8
IP Rating	IP65	IK Rating	IK10



PHOTOMETRICS					
Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
WPCSBK	Standard	17 W	3000 K	1580 lm	93 lm/W
			4000 K	1645 lm	97 lm/W
			6000 K	1595 lm	94 lm/W
WPCSBKPC	Photocell	17 W	3000 K	1580 lm	93 lm/W
			4000 K	1645 lm	97 lm/W
			6000 K	1595 lm	94 lm/W
WPCSWH	Standard	17 W	3000 K	1580 lm	93 lm/W
			4000 K	1645 lm	97 lm/W
			6000 K	1595 lm	94 lm/W
WPCSWHPC	Photocell	17 W	3000 K	1580 lm	93 lm/W
			4000 K	1645 lm	97 lm/W
			6000 K	1595 lm	94 lm/W

PACKAGING	
Packaging Type	Plain Box
Individual unit gross weight	734 g
Pallet Qty	0
MOM / OPQ	1 / 10



IP65



IK10



Colour Temp.
Selectable

