

Spec Sheet WPCSWHPC







Slim Wallpack

Slim white IP65 wall pack 17W CCT selectable with photocell

DESCRIPTION

Slim profile and durable wall pack, available with colour temperature selection to suit different applications. The design offers a contemporary slimmer update to the traditional wall pack available with further energy savings with an option of an integrated photocell

FEATURES

- Colour temperature selectable 3000K, 4000K, 6000K
- Up to 90 lm/W
- ABS base and polycarbonate diffuser
- Slim design
- Opal diffuser, evenly diffused light output
- 20mm cable entries on either side and one to the rear
- Photocell for dusk to dawn operation

GENERAL INFORMATION			
Light Source	LED	**Colour / Finish**	White
Application	External	**Mounting Type**	Surface
Product Warranty	5 Years	**Net Weight**	0.5 kg
Energy Efficiency Class	E		

TECHNICAL INFORMATION			
Nominal Voltage	240	**Frequency**	50Hz
Class Protection	2	**Operating Temperature (Min)**	-20 °C
Operating Temperature (Max)	45 °C	**Average Rated Life**	50,000 h
Number of switching cycles	25,000	**Construction Materials Line 1**	Polycarbonate
Construction Materials Line 2	ABS	**Dimensions - Height**	275 mm
Dimensions - Width	185 mm	**Dimensions - Depth**	70 mm
IK Rating	IK10	**IP Rating**	IP65

PRODUCT INFORMATION			
Wattage Combined	17W	**CCT Combined**	3000K / 4000K / 6000K
Luminaire Lumens Combined	1580 - 1595 lm	**lm/W Combined**	93 - 94 lm/w
Beam Angle	120°	**CRI**	80
SDCM	<6	**Lumen Maintenance**	0.8

5 Year Warranty

IP65

IK10

Colour Temp. Selectable

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

Spec Sheet WPCSWHPC

Lighting Technology used	LED	**Non-Directional or Directional**	NDLS
Mains or non-mains	MLS	**Connected light source (CLS)**	FALSE
Colour tuneable light source	FALSE	**High Luminance light source**	FALSE
Anti Glare shield	FALSE	**Dimmable**	Not Dimmable
Correlated Colour temperature type	STEPS	**Correlated Colour temperature (K) 1**	3,000
Correlated Colour temperature (K) 2	4,000	**Correlated Colour temperature (K) 3**	6,000
Chromaticity coordinates x	0.434	**Chromaticity coordinates y**	0.405
Stroboscopic effect metric (SVM)	0	**Flicker Metric (pst)**	0.5
R9 colour rendering index	10	**Survival factor @6000hrs**	0.9
Spectrum report available	Yes	**Displacement Factor**	0.92
CCT1/WATT1: Rated Peak Intensity	385 cd	**CCT2/WATT1: Rated Peak Intensity**	412 cd
CCT3/WATT1: Rated Peak Intensity	394 cd		

5 Year Warranty

IP65

IK10

Colour Temp. Selectable

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

PHOTOMETRICS					
Product Code	**Product Type**	**Watts**	**CCT**	**Luminaire lumens**	**Lm/W**
WPCSBK	Standard, Black	15 W	3000 K	1580 lm	105 lm/W
			4000 K	1645 lm	110 lm/W
			6000 K	1595 lm	106 lm/W
WPCSBKPC	Photocell, Black	15 W	3000 K	1580 lm	105 lm/W
			4000 K	1645 lm	110 lm/W
			6000 K	1595 lm	106 lm/W
WPCSWH	White	17 W	3000 K	1580 lm	93 lm/W
			4000 K	1645 lm	97 lm/W
			6000 K	1595 lm	94 lm/W
WPCSWHPC	Photocell, White	17 W	3000 K	1580 lm	93 lm/W
			4000 K	1645 lm	97 lm/W
			6000 K	1595 lm	94 lm/W

PACKAGING	
Packaging Type	Plain Box
Individual unit gross weight	734 g
Pallet Layer Qty	100
Pallet Layers	3
Pallet Qty	300
MOM / OPQ	1 / 10

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D