



5FT LED Step-Dim
Weatherproof Fitting


5ft 30W 5000K LED Step-Dim Weatherproof
Fitting

DESCRIPTION

Superb one for one replacement for traditional fluorescent
fixtures

FEATURES

- Polycarbonate housing and diffuser
- Multiple fixing options - supplied with surface mounting brackets and suspension hooks
- Gear tray retaining strap for easy installation. Push-fit terminal block. Stainless steel clips
- Detection Area 10% / 50% / 75% / 100%
- Hold Time 5s / 30s / 1 min / 5 min / 10 min / 20 min / 30 min
- Stand By Period 0s / 10s / 1 min / 10 min / 30 min / 1hr / 8
- Standby Dimming Level 10% / 20% / 30% / 50%
- Daylight Threshold 2 lux / 10 lux / 50 lux / Disable
- Detection Area - Max 14m (ceiling mount) Max 10m (wall mount)



GENERAL INFORMATION

Light Source	LED	Colour / Finish	Grey
Application	Internal/External	Mounting Type	Surface, Suspended
Product Warranty	5 Years	Net Weight	2.25 kg
Energy Efficiency Class	E		

TECHNICAL INFORMATION

Nominal Voltage	240 V	Frequency	50Hz
Class Protection	1	Average Rated Life	30,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Polycarbonate
Dimensions - Height	95 mm	Dimensions - Width	1560 mm
Dimensions - Depth	90 mm		

PRODUCT INFORMATION

Wattage Combined	30W	CCT Combined	5000K
Luminaire Lumens Combined	3000 lm	lm/W Combined	100 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
IP Rating	IP65		



PHOTOMETRICS					
Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
WPLED51SD	On / Off Microwave	30 W	5000 K	3000 lm	100 lm/W
WPLED61SD	On / Off Microwave	40 W	5000 K	4000 lm	100 lm/W

PACKAGING	
Packaging Type	Plain Box
Individual unit gross weight	2,607 g
Pallet Qty	0
MOM / OPQ	1 / 6

