

## 6FT LED Step-Dim Weatherproof Fitting

6ft 40W 5000K LED Step-Dim Weatherproof Fitting




### DESCRIPTION

Superb one for one replacement for traditional fluorescent fixtures

### FEATURES

- Polycarbonate housing and diffuser
- Multiple fixing options - supplied with surface mounting brackets and suspension hooks
- Gear tray retaining strap for easy installation. Push-fit terminal block. Stainless steel clips
- Detection Area 10% / 50% / 75% / 100%
- Hold Time 5s / 30s / 1 min / 5 min / 10 min / 20 min / 30 min
- Stand By Period 0s / 10s / 1 min / 10 min / 30 min / 1hr / 8
- Standby Dimming Level 10% / 20% / 30% / 50%
- Daylight Threshold 2 lux / 10 lux / 50 lux / Disable
- Detection Area - Max 14m (ceiling mount) Max 10m (wall mount)



### GENERAL INFORMATION

Light Source	LED	Colour / Finish	Grey
Application	Internal/External	Mounting Type	Surface, Suspended
Product Warranty	5 Years	Net Weight	2.7 kg
Energy Efficiency Class	E		

### TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50Hz
Class Protection	1	Average Rated Life	30,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Polycarbonate
Dimensions - Height	95 mm	Dimensions - Width	1830 mm
Dimensions - Depth	90 mm	IP Rating	IP65

### PRODUCT INFORMATION

Wattage Combined	40W	CCT Combined	5000K
Luminaire Lumens Combined	4000 lm	lm/W Combined	100 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
Dimmable	Not Dimmable	CCT1/WATT1: Rated Peak Intensity	1,425 cd





PHOTOMETRICS					
Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
WPLED51SD	On / Off Microwave	30	5000 K	3000 lm	100 lm/W
WPLED61SD	On / Off Microwave	40	5000 K	4000 lm	100 lm/W

PACKAGING	
Packaging Type	Plain Box
Individual unit gross weight	3,014 g
Pallet Layer Qty	24
Pallet Layers	4
Pallet Qty	96
MOM / OPQ	1 / 6

