
Spec Sheet WPLED61SD

5 Year Warranty

IP65





6FT LED Step-Dim Weatherproof Fitting

6ft 40W 5000K LED Step-Dim Weatherproof Fitting

DESCRIPTION

Superb one for one replacement for traditional fluorescent fixtures

FEATURES

- Polycarbonate housing and diffuser
- Multiple fixing options - supplied with surface mounting brackets and suspension hooks
- Gear tray retaining strap for easy installation. Push-fit terminal block. Stainless steel clips
- Detection Area 10% / 50% / 75% / 100%
- Hold Time 5s / 30s / 1 min / 5 min / 10 min / 20 min / 30 min
- Stand By Period 0s / 10s / 1 min / 10 min / 30 min / 1hr / 8
- Standby Dimming Level 10% / 20% / 30% / 50%
- Daylight Threshold 2 lux / 10 lux / 50 lux / Disable
- Detection Area - Max 14m (ceiling mount) Max 10m (wall mount)

GENERAL INFORMATION			
Light Source	LED	**Colour / Finish**	Grey
Application	Internal/External	**Mounting Type**	Surface, Suspended
Product Warranty	5 Years	**Net Weight**	2.7 kg
Energy Efficiency Class	E		

TECHNICAL INFORMATION			
Nominal Voltage	240	**Frequency**	50Hz
Class Protection	1	**Average Rated Life**	30,000 h
Number of switching cycles	15,000	**Construction Materials Line 1**	Polycarbonate
Dimensions - Height	95 mm	**Dimensions - Width**	1830 mm
Dimensions - Depth	90 mm	**IP Rating**	IP65

PRODUCT INFORMATION			
Wattage Combined	40W	**CCT Combined**	5000K
Luminaire Lumens Combined	4000 lm	**lm/W Combined**	100 lm/w
Beam Angle	120°	**CRI**	80
SDCM	<6	**Lumen Maintenance**	0.7
Dimmable	Not Dimmable	**CCT1/WATT1: Rated Peak Intensity**	1,425 cd

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

5 Year Warranty

IP65

PHOTOMETRICS					
Product Code	**Product Type**	**Watts**	**CCT**	**Luminaire lumens**	**Lm/W**
WPLED51SD	On / Off Microwave	30 W	5000 K	3000 lm	100 lm/W
WPLED61SD	On / Off Microwave	40 W	5000 K	4000 lm	100 lm/W

PACKAGING	
Packaging Type	Plain Box
Individual unit gross weight	3,014 g
Pallet Layer Qty	24
Pallet Layers	4
Pallet Qty	96
MOM / OPQ	1 / 6