




ANTI-SLIP

Anti-Slip Adhesive Tape



PROPERTIES

Permanent use in indoor and outdoor areas.
Anti-slip adhesive tapes.
Self adhesive.

PROCESSING

1. The surface must be cleaned. Any contaminants such as release agents, preservatives, grease, oil, dust, water, old adhesives/sealants and other residues that could impair adhesion must be completely removed.
2. Remove the protective film from the adhesive strip, align the tape and stick it in the desired position.

The generally accepted rules of technology and tiling must be observed. Suitability for use with mechanical and chemical resistance must always be checked in each individual case.

TECHNICAL DIMENSIONS AND PRODUCT VARIANTS

Material	[PVC]
Surface	[anti-slip]
Colour	black, black/yellow

Please note: For technical reasons, tolerances in color effects of the materials and print are possible.
All information is based on the best of our knowledge and belief. No guarantee can be derived from this.
We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.



Length	500 cm
Width mm	25 mm, 50 mm

PRODUCT VARIANTS

Ident	Surface	Colour	Length
AS 2533	anti-slip	black	500 cm
AS 5033	anti-slip	black	500 cm
AS 2589	anti-slip	black/yellow	500 cm
AS 5089	anti-slip	black/yellow	500 cm

Please note: For technical reasons, tolerances in color effects of the materials and print are possible.
 All information is based on the best of our knowledge and belief. No guarantee can be derived from this.
 We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.