




DURABAL BK

Internal Corner For The DURABAL BK Balcony Angle Profile With Drip Sill



MATERIAL

Aluminium can be used wherever a medium mechanical stresses are expected. Contact with alkaline materials (e.g. tile adhesive) can lead to discolouration, which can be difficult to remove afterwards. High humidity during the drying phase can intensify this process. Always wipe off tile adhesive or grout on visible surfaces immediately with plenty of water, then wipe dry and ensure that the room is well ventilated.

Suitability in terms of mechanical and chemical resistance must always be checked on a case-by-case basis.

CARE

Aluminium does not require any special care. If necessary, it can simply be damp-cleaned with clear, clean water and a few drops of washing-up liquid. Then wipe dry.

Acidic, alkaline and abrasive cleaning agents should be avoided.

PROCESSING

1. Select and adjust the profile according to the desired covering and installation height.
2. Apply tile adhesive to the substrate (concrete slab or dry screed) using a notched trowel.
3. Press the profile into the adhesive bed and align it in height and alignment.
4. Use suitable external and internal corners if required. Use the connectors available as accessories to connect several profiles.
5. Fill the fixing flanges completely with adhesive.
6. Press the covering firmly into place and align it so that it is flush with the top edge of the profile.
7. Leave a 1-2 mm gap between the profile and the covering.
8. Fill the space between the tiles and the profile completely with joint mortar.

Protect visible surfaces from contact with tile adhesive or joint mortar and clean immediately with a cloth and clear water if necessary. Then rub dry.

Please note: For technical reasons, tolerances in color effects of the materials and print are possible. All information is based on the best of our knowledge and belief. No guarantee can be derived from this. We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.



The generally accepted rules of technology and tiling must be observed. Suitability for use with mechanical and chemical resistance must always be checked in each individual case.

TECHNICAL DIMENSIONS AND PRODUCT VARIANTS

Material	[Aluminium]
Surface	[powder coated], [anodised]
Colour	silver, anthracite, anthracite grey (RAL 7016)
Height	22 mm
dimension	Internal Dimension 15 x 15 mm, Internal Dimension 17 x 17 mm

PRODUCT VARIANTS

Ident	Height	Surface	Colour
BKAE 220-60-XIH	22 mm	anodised	silver
BKAC 22016-60-XIH	22 mm	powder coated	anthracite
BKAE 60-XIH/1		anodised	silver
BKAE-XIH/1		anodised	silver
BKAE-XIH/10		anodised	silver
BKAC 60-XIH/1		powder coated	anthracite grey (RAL 7016)
BKAC-XIH/1		powder coated	anthracite grey (RAL 7016)

Please note: For technical reasons, tolerances in color effects of the materials and print are possible. All information is based on the best of our knowledge and belief. No guarantee can be derived from this. We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.