




# DURABAL BO

## T-Shaped Balcony Angle Profile For Installation With Supports



### TECHNICAL DIMENSIONS AND PRODUCT VARIANTS

Material	Aluminium
Surface	powder coated, anodised
Colour	silver, light ivory (RAL 1015), anthracite grey (RAL 7016)
Length	300 cm
Height (b)	40 mm, 60 mm, 80 mm, 100 mm, 120 mm
Width mm	80 mm

### ACCESSORIES

Matching corner pieces and connectors are available as accessories.

### MATERIAL

Aluminium can be used wherever a medium mechanical stresses are expected. Contact with alkaline materials (e.g. tile adhesive) can lead to discolouration, which can be difficult to remove afterwards. High humidity during the drying phase can intensify this process. Always wipe off tile adhesive or grout on visible surfaces immediately with plenty of water, then wipe dry and ensure that the room is well ventilated.

Suitability in terms of mechanical and chemical resistance must always be checked on a case-by-case basis.

### CARE

Aluminium does not require any special care. If necessary, it can simply be damp-cleaned with clear, clean water and a few drops of washing-up liquid. Then wipe dry.

Acidic, alkaline and abrasive cleaning agents should be avoided.

### PROCESSING

Installation on supports:

1. Position and adjust the supports according to the conditions. Create a straight edge at the predetermined breaking point on the supports adjacent to the profile.
2. Select and adjust the profile according to the desired installation height.
3. Place the profile on the pedestal support and align it in height and alignment. If necessary, fix it with the polymer adhesive

09 May 2025 07:03 PM

Please note: For technical reasons, tolerances in color effects of the materials and print are possible.  
All information is based on the best of our knowledge and belief. No guarantee can be derived from this.  
We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.



SPEEDFLEX, for example.

4. If necessary, use appropriate external or internal corners.
5. Several profiles can be joined together using the connectors available as accessories.
6. Finally, lay the covering professionally on the pedestal supports.

Thin-bed installation:

1. Select and adjust the profile according to the required installation height.
2. Apply tile adhesive to the substrate (concrete slab or dry screed) using a notched trowel.
3. Press the profile into the adhesive bed and check height and alignment.
4. If necessary, use suitable external and internal corners. To connect several profiles, use the connectors available as accessories.
5. Cover the entire surface of the fastening leg with adhesive.
6. Press the covering firmly into place and align it so that it is flush with the profile edge.
7. Leave a joint of 1-2 mm to the profile.
8. Completely fill the space between the tiles and the profile with grout. Protect visible surfaces from contact with tile adhesive or grout and, if necessary, clean immediately with a sponge and clean water. Then rub dry.

In both types of installation, the generally recognised rules of technology must be observed. The suitability with regard to mechanical and chemical resistance must always be checked in each individual case.

## PRODUCT VARIANTS

Ident	Height (b)	Surface	Colour	Length
BOAE 20-20/300	40 mm	anodised	silver	300 cm
BOAC 4016/300	40 mm	powder coated	anthracite grey (RAL 7016)	300 cm
BOAC 4015/300	40 mm	powder coated	light ivory (RAL 1015)	300 cm
BOAE 20-40/300	60 mm	anodised	silver	300 cm
BOAC 6016/300	60 mm	powder coated	anthracite grey (RAL 7016)	300 cm
BOAC 6015/300	60 mm	powder coated	light ivory (RAL 1015)	300 cm
BOAE 20-60/300	80 mm	anodised	silver	300 cm
BOAC 8016/300	80 mm	powder coated	anthracite grey (RAL 7016)	300 cm
BOAC 8015/300	80 mm	powder coated	light ivory (RAL 1015)	300 cm
BOAE 20-80/300	100 mm	anodised	silver	300 cm
BOAC 10016/300	100 mm	powder coated	anthracite grey (RAL 7016)	300 cm
BOAC 10015/300	100 mm	powder coated	light ivory (RAL 1015)	300 cm
BOAE 20-100/300	120 mm	anodised	silver	300 cm
BOAC 12016/300	120 mm	powder coated	anthracite grey (RAL 7016)	300 cm
BOAC 12015/300	120 mm	powder coated	light ivory (RAL 1015)	300 cm

09 May 2025 07:03 PM

Please note: For technical reasons, tolerances in color effects of the materials and print are possible.  
All information is based on the best of our knowledge and belief. No guarantee can be derived from this.  
We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.