



# **DURACOVE TW**

## Concave Trim In PVC









#### **MATERIAL**

PVC is particularly suitable for indoor and outdoor areas with low mechanical loads. The material is dyed throughout and is therefore UV-resistant under normal circumstances. However, colour differences may occur with constant UV exposure.

The applicability with regard to mechanical and chemical resistance must always be checked on a case-by-case basis.

Note: When using coloured joint mortar with ultra-fine colour pigments in conjunction with plastic profiles, irreversible profile staining may occur. We recommend the use of appropriate protective measures

#### **CARE**

PVC does not require any special care. It can be cleaned as needed with just clear, clean water with a few drops of washing-up liquid added.

Solvent-based and abrasive cleaning agents should be avoided.

#### **PROCESSING**

- 1. The bonding surfaces must be cleaned and any contamination such as release agents, preservatives, grease, oil, dust, water, old adhesives/sealants and other substances that could impair adhesion must be removed.
- 2. Apply SPEED-FLEX adhesive sealant or a suitable alternative to the adhesive sides of the profile. In terms of installation, the internal or external corner pieces should be attached first, then the profile should be inserted in without a joint.
- 3. Place the profile flush in the corner and press firmly.
- 4. Mitre the profile to form the corner. Seal the mitre joint with a neutral-curing silicone.
- 5. Close the open ends with the appropriate end caps.
- 6. Allow any adhesive sealant that has escaped to dry, then carefully cut along the profile edge with a sharp knife without damaging the substrate and then remove.

Note: The profile does not replace sealing/waterproofing. If necessary, this must be carried out separately using suitable measures.

The generally recognised rules of technology must be observed. The suitability with regard to mechanical and chemical resistance must

Please note: For technical reasons, tolerances in color effects of the materials and print are possible.

All information is based on the best of our knowledge and belief. No guarantee can be derived from this.

We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.

**DURAL GmbH** | Südring 11 | D-56412 Ruppach-Goldhausen | Germany | +49 2602/9261-0 | info@dural.com **DURAL Ltd.** | Unit 6a | Wakefield Business Centre Denby Dale Rd | Wakefield | WF2 7AZ | United Kingdom | ukinfo@dural.com





always be checked in each individual case.

## TECHNICAL DIMENSIONS AND PRODUCT VARIANTS

Material	[PVC]
Colour	white
Length	183 cm
Height	38.5 mm
Width mm	23 mm

## **PRODUCT VARIANTS**

1	dent	Height	Colour	Length
I	DCP 4030/183	38.5 mm	white	183 cm

Please note: For technical reasons, tolerances in color effects of the materials and print are possible.

All information is based on the best of our knowledge and belief. No guarantee can be derived from this.

We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.