



DURALIS-LED

Translucent Cover For Led-Lightable Duralis Profile



MATERIAL

Polycarbonate

CARE

Polycarbonate does not require any special care. If necessary, it can be cleaned with clear, clean water and a few drops of washing-up liquid. Then wipe dry.

PROCESSING

1. Cut the cover and adhesive tape to size as required.
2. The substrate must be cleaned and any contaminants such as release agents, preservatives, grease, oil, dust, water, old adhesives/sealants and other substances that impair adhesion must be removed.
3. Remove the protective film from the adhesive strip and stick it in the desired position. First, apply the adhesive tape to the cover and then stick it to the profile.

The generally accepted rules of technology and tiling must be observed. Suitability for use with mechanical and chemical resistance must always be checked in each individual case.

TECHNICAL DIMENSIONS AND PRODUCT VARIANTS

Material	[Polycarbonate]
----------	-----------------

Please note: For technical reasons, tolerances in color effects of the materials and print are possible. All information is based on the best of our knowledge and belief. No guarantee can be derived from this. We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.



Surface	[translucent]
Colour	white, black, grey
Length	250 cm
sight width	16 mm
Height	4 mm
Width mm	16 mm

PRODUCT VARIANTS

Ident	Height	Surface	Colour	Length
DLP LED 1433/250	4 mm	translucent	black	250 cm
DLP LED 1430/250	4 mm	translucent	white	250 cm
DLP LED 1438/250	4 mm		grey	

Please note: For technical reasons, tolerances in color effects of the materials and print are possible.
 All information is based on the best of our knowledge and belief. No guarantee can be derived from this.
 We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.