


DURASTEP SOLID Stainless Steel (304)


DURAL

Stainless Steel Stair Nosing Profile









ACCESSORIES

Matching end caps are available as accessories

PROPERTIES

DGUV-Test IFA 2404171: Rutschhemmklasse R11, Verdrängungsraum V6

MATERIAL

Stainless steel (V2A/304) is particularly suitable for areas of application subject to high mechanical loads and where particularly high demands are placed on cleanliness, hygiene and chemical resistance. Contact with products containing hydrochloric acid should be avoided.

Tools made of unalloyed steel must not be used during processing. Open cut edges are not rust-resistant. If necessary, separate rust protection must be applied there.

Depending on the environmental conditions, rust film may also form on stainless steel and should be removed immediately.

The usability in terms of mechanical and chemical resistance must always be checked on a case-by-case basis.

CARE

Stainless steel (V2A/304) does not require any special care. If necessary, it can simply be cleaned with clear, clean water and a few drops of washing-up liquid. Then wipe dry.

Acidic and abrasive cleaning agents should be avoided. Flash rust can be removed with commercially available polishes suitable for stainless steel.

PROCESSING

- 1. Cut the profiles to size. Align the basic trim on the floor, mark it and mark the drill holes.
- 2. Secure the basic trim to the marked position using screws and dowels.
- 3. Lay the floor covering with sufficient expansion joint spacing.
- 4. Place the top profile on the basic trim.
- 5. Screw the top profile onto the basic trim.

It will adjust to the respective height.

Please note: For technical reasons, tolerances in color effects of the materials and print are possible.

All information is based on the best of our knowledge and belief. No guarantee can be derived from this.

We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.

DURAL GmbH | Südring 11 | D-56412 Ruppach-Goldhausen | Germany | +49 2602/9261-0 | info@dural.com **DURAL Ltd.** | Unit 6a | Wakefield Business Centre Denby Dale Rd | Wakefield | WF2 7AZ | United Kingdom | ukinfo@dural.com





The generally accepted rules of technology and tiling must be observed. Suitability for use with mechanical and chemical resistance must always be checked in each individual case..

TECHNICAL DIMENSIONS AND PRODUCT VARIANTS

Material	[Stainless Steel (304)]		
Surface	[natural]		
Colour	natural		
Length	150 cm, 250 cm		
sight width	30 mm		
Height	9 mm, 11 mm		
Width mm	30 mm		

PRODUCT VARIANTS

Ident	Height	Surface	Colour	Length
DSTOE 90/150	9 mm	natural	natural	150 cm
DSTOE 90/250	9 mm	natural	natural	250 cm
DSTOE 110/150	11 mm	natural	natural	150 cm
DSTOE 110/250	11 mm	natural	natural	250 cm

Please note: For technical reasons, tolerances in color effects of the materials and print are possible.

All information is based on the best of our knowledge and belief. No guarantee can be derived from this.

We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.