



DURAWAY

Angle Frames For Doormats



PROPERTIES

Mat frame

Angle thicknesses:

Stainless steel: 2 and 3 mm

Aluminium: 3 mm

Angle height:

Stainless steel: 20, 25 and 30 mm

Aluminium: 13, 20, 25 and 30 mm

Angle width:

Stainless steel: 20, 25 and 30 mm

Aluminium: 25 and 30 mm

MATERIAL

DWRE=stainless steel, DWRA=aluminium

Aluminium can be used wherever medium mechanical stress is to be expected. Contact with alkaline materials (e.g. tile adhesive) can lead to discolouration, which is difficult to remove afterwards. High humidity during the drying phase can intensify this process. Always wipe tile adhesive or grout off visible surfaces immediately with plenty of water, then wipe dry and ensure good room ventilation.

Stainless steel V2A/304 is particularly suitable for applications subject to high mechanical stress and for applications with particularly high requirements for cleanliness, hygiene and chemical resistance. Contact with products containing hydrochloric acid must be avoided.

Do not use tools made of unalloyed steel during processing. Open cut edges are not rust-resistant. If necessary, separate rust protection should be applied.

Even with stainless steel, flash rust is possible depending on the environmental conditions and should be removed immediately.

The suitability with regard to mechanical and chemical resistance must always be checked in individual cases.

Suitability with regard to mechanical and chemical resistance must always be checked on a case-by-case basis.

CARE

Please note: For technical reasons, tolerances in color effects of the materials and print are possible.
All information is based on the best of our knowledge and belief. No guarantee can be derived from this.
We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.

DURAL GmbH | Südring 11 | D-56412 Ruppach-Goldhausen | Germany | +49 2602/9261-0 | info@dural.com

DURAL Ltd. | Unit 6a | Wakefield Business Centre Denby Dale Rd | Wakefield | WF2 7AZ | United Kingdom | ukinfo@dural.com

The recognised standards and regulations of technology must be observed. Previous data sheets are invalid.

www.dural.com



Aluminium does not require any special care. If necessary, it can be cleaned with clear, clean water and a few drops of washing-up liquid. Then wipe dry.

Avoid using acidic, alkaline and abrasive cleaning agents.

Stainless steel (304) does not require any special care. If necessary, it can be cleaned with clear, clean water and a few drops of washing-up liquid. Then wipe dry.

Avoid using acidic, alkaline and abrasive cleaning agents. Flash rust can be removed with commercially available polishes suitable for stainless steel.

PROCESSING

1. Assemble the DURAWAY mat frame using the screw connections.
2. Insert the frame into the intended opening and install it precisely to the required height.
3. The tiles can then be laid on the frame. Ensure that the surface is flush and that there is a joint width of 2–3 mm all around.
4. Once the laying mortar has dried completely, the surface can be grouted.
5. Once the joints are complete and completely dry, the DURAWAY doormat can be inserted.

Protect visible frame surfaces from contact with tile adhesive or joint mortar. If necessary, remove any dirt immediately with a cloth and clear water and then rub dry.

The generally accepted rules of technology must be observed.

The suitability with regard to mechanical and chemical loads must always be checked in each individual case.

TECHNICAL DIMENSIONS AND PRODUCT VARIANTS

Material	[Aluminium], [Stainless Steel (304)]
Height	11 mm, 13 mm, 20 mm, 25 mm, 30 mm
Width mm	20 mm, 25 mm, 30 mm
Strength mm	2, 3
dimension	13 x 30 x 3 mm, 20 x 30 x 3 mm, 25 x 25 x 3 mm, 30 x 30 x 3 mm, 11 x 30 x 2 mm, 20 x 20 x 3 mm

PRODUCT VARIANTS

Ident	Height
DWRE 1030	11 mm
DWRA 1030	13 mm

Please note: For technical reasons, tolerances in color effects of the materials and print are possible. All information is based on the best of our knowledge and belief. No guarantee can be derived from this. We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.



DWRA 1730	20 mm
DWRE 1720	20 mm
DWRA 2225	25 mm
DWRE 2225	25 mm
DWRA 2730	30 mm
DWRE 2730	30 mm

Please note: For technical reasons, tolerances in color effects of the materials and print are possible.
All information is based on the best of our knowledge and belief. No guarantee can be derived from this.
We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.