



LED-Cover

Translucent Cover For Led Illuminated Stair Profiles



PROPERTIES

Translucent cover for CONSTRUCT-LED, SQUARESTEP-LED and FLORENTOSTEP-LED
Adhesive (double-sided) strip factory-applied to one side

MATERIAL

Polycarbonate

CARE

Polycarbonate does not require any special care. If necessary, it can be cleaned with clear, clean water and a few drops of washing-up liquid. Then wipe dry.

PROCESSING

1. Cut the cover to size.
2. The profile must be cleaned and any contaminants such as release agents, preservatives, grease, oil, dust, water, old adhesives/sealants and other substances that impair adhesion must be removed.
3. Remove the protective film from the adhesive strip and stick it to the desired position in the profile.

The generally accepted rules of technology and tiling must be observed. Suitability for use with mechanical and chemical resistance must always be checked in each individual case.

TECHNICAL DIMENSIONS AND PRODUCT VARIANTS

Please note: For technical reasons, tolerances in color effects of the materials and print are possible.
All information is based on the best of our knowledge and belief. No guarantee can be derived from this.
We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.



Material	[Polycarbonate]
Surface	[translucent]
Colour	white, black, grey
Length	250 cm
Height	9.5 mm, 11 mm
Width mm	10.5 mm, 10 mm

PRODUCT VARIANTS

Ident	Height	Surface	Colour	Length
FSTP LED 1033/250	9.5 mm	translucent	black	
FSTP LED 1038/250	11 mm	translucent	grey	250 cm
FSTP LED 1030/250	11 mm	translucent	white	250 cm

Please note: For technical reasons, tolerances in color effects of the materials and print are possible. All information is based on the best of our knowledge and belief. No guarantee can be derived from this. We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.