




SHOWER-GK CONNECT

Wall Connection Trim For Inclined Wedges



MATERIAL

Stainless steel (304) is particularly suitable for applications subject to high mechanical stress and for applications with particularly high requirements for cleanliness, hygiene and chemical resistance. Contact with products containing hydrochloric acid should be avoided.

No tools made of unalloyed steel may be used for processing. Open cut edges are not rust-resistant. If necessary, separate rust protection must be applied.

Even with stainless steel, flash rust may occur depending on the environmental conditions and should be removed immediately. The suitability of the material with regard to mechanical and chemical resistance must always be checked in individual cases. The suitability for mechanical and chemical stress must always be checked on a case-by-case basis.

CARE

Stainless steel V2A/304 does not require any special care. If necessary, it can be cleaned simply with clear, clean water and a few drops of washing-up liquid. Then wipe dry.

Avoid using acidic, alkaline and abrasive cleaning agents. Flash rust can be removed with commercially available polishes suitable for stainless steel.

PROCESSING

1. Select the height of the profile according to the gradient.
2. Apply sufficient tile adhesive.
3. Press the profile in until both surfaces (tiles and profile) are flush.
4. Lay the wall tiles.
5. Leave a 1-2 mm joint between the profile and the tiles.
6. Fill the space between the tiles and the profile completely with grout.

To cut stainless steel profiles, use a slow-running angle grinder with a suitable, clean cutting disc. Prevent cutting sparks from depositing on the profile surfaces.

Please note: For technical reasons, tolerances in color effects of the materials and print are possible. All information is based on the best of our knowledge and belief. No guarantee can be derived from this. We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.



Protect visible surfaces from contact with tile adhesive or joint mortar and clean immediately with a cloth and clear water if necessary. Then rub dry.

The generally accepted rules of technology must be observed.

The generally accepted rules of technology and tiling must be observed. Suitability for use with mechanical and chemical resistance must always be checked in each individual case.

TECHNICAL DIMENSIONS AND PRODUCT VARIANTS

Material	[Stainless Steel (304)]
Surface	[tactile coated], [brushed]
Colour	natural, concrete grey (RAL 0006500), white matt (RAL 9003), black matt (RAL 9005), sand (RAL 0808005)
Length	100 cm, 150 cm
Height	8 mm
Width mm	20 mm, 30 mm, 40 mm

PRODUCT VARIANTS

Ident	Height	Surface	Colour	Length
GKW 200-SF/100	8 mm	brushed	natural	100 cm
GKW 300-SF/100	8 mm	brushed	natural	100 cm
GKW 400-SF/100	8 mm	brushed	natural	100 cm
GKW 200-SF/150	8 mm	brushed	natural	150 cm
GKW 300-SF/150	8 mm	brushed	natural	150 cm
GKW 400-SF/150	8 mm	brushed	natural	150 cm
GKW 200-11/100	8 mm	tactile coated	black matt (RAL 9005)	100 cm
GKW 300-11/100	8 mm	tactile coated	black matt (RAL 9005)	100 cm
GKW 400-11/100	8 mm	tactile coated	black matt (RAL 9005)	100 cm
GKW 200-11/150	8 mm	tactile coated	black matt (RAL 9005)	150 cm
GKW 300-11/150	8 mm	tactile coated	black matt (RAL 9005)	150 cm
GKW 400-11/150	8 mm	tactile coated	black matt (RAL 9005)	150 cm
GKW 200-65/100	8 mm	tactile coated	concrete grey (RAL 0006500)	100 cm
GKW 300-65/100	8 mm	tactile coated	concrete grey (RAL 0006500)	100 cm

Please note: For technical reasons, tolerances in color effects of the materials and print are possible. All information is based on the best of our knowledge and belief. No guarantee can be derived from this. We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.



GKW 400-65/100	8 mm	tactile coated	concrete grey (RAL 0006500)	100 cm
GKW 200-65/150	8 mm	tactile coated	concrete grey (RAL 0006500)	150 cm
GKW 300-65/150	8 mm	tactile coated	concrete grey (RAL 0006500)	150 cm
GKW 400-65/150	8 mm	tactile coated	concrete grey (RAL 0006500)	150 cm
GKW 200-80/100	8 mm	tactile coated	sand (RAL 0808005)	100 cm
GKW 300-80/100	8 mm	tactile coated	sand (RAL 0808005)	100 cm
GKW 400-80/100	8 mm	tactile coated	sand (RAL 0808005)	100 cm
GKW 200-80/150	8 mm	tactile coated	sand (RAL 0808005)	150 cm
GKW 300-80/150	8 mm	tactile coated	sand (RAL 0808005)	150 cm
GKW 400-80/150	8 mm	tactile coated	sand (RAL 0808005)	150 cm
GKW 200-12/100	8 mm	tactile coated	white matt (RAL 9003)	100 cm
GKW 300-12/100	8 mm	tactile coated	white matt (RAL 9003)	100 cm
GKW 400-12/100	8 mm	tactile coated	white matt (RAL 9003)	100 cm
GKW 200-12/150	8 mm	tactile coated	white matt (RAL 9003)	150 cm
GKW 300-12/150	8 mm	tactile coated	white matt (RAL 9003)	150 cm
GKW 400-12/150	8 mm	tactile coated	white matt (RAL 9003)	150 cm

Please note: For technical reasons, tolerances in color effects of the materials and print are possible.
 All information is based on the best of our knowledge and belief. No guarantee can be derived from this.
 We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.