EN Datasheet

MAXIFLOOR

Extra-Wide Transition Profile Made Of Aluminium






ACCESSORIES

Screws/dowels for fastening MAXIFLOOR profiles in 270 cm length
Dimensions: 3.0 x 25 mm
for drill bit Ø 4.0 mm

PROPERTIES

For screwing, incl. fastening material for the 100 cm profiles
Or self adhesive. Without visible fastening

MATERIAL

Aluminium can be used wherever medium mechanical stress is to be expected. Contact with alkaline materials (e.g. tile adhesive) can lead to discolouration, which is difficult to remove afterwards. High humidity can intensify this process. Dirt deposits can be removed with standard cleaning agents. Cleaning agents must be free of scouring powder or aggressive additives.

The suitability with regard to mechanical and chemical resistance must always be checked in each individual case.

CARE

Aluminium does not require any special care. If necessary, it can be cleaned with clear, clean water and a drop of washing-up liquid. Then wipe dry.

Avoid using acidic, alkaline and abrasive cleaning agents.

PROCESSING

1. Cut the profiles to size. For non-self-adhesive profiles, align the profile on the floor, mark it and mark the drill holes.
2. For non-self-adhesive profiles, drill holes at the marked points.
3. For non-self-adhesive profiles, fasten the profile to the drilled location using screws and dowels.
4. For self-adhesive profiles, the substrate must be cleaned of any contaminants such as release agents, preservatives, grease, oil, dust, water, old adhesives/sealants and other substances that could impair adhesion.
5. For self-adhesive profiles, remove the protective film from the adhesive strip, align the profile and stick it to the desired location.

The generally accepted rules of technology and tiling must be observed. Suitability for use with mechanical and chemical resistance must always be checked in each individual case..

Please note: For technical reasons, tolerances in color effects of the materials and print are possible.
All information is based on the best of our knowledge and belief. No guarantee can be derived from this.
We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.

DURAL GmbH | Südring 11 | D-56412 Ruppach-Goldhausen | Germany | +49 2602/9261-0 | info@dural.com
DURAL Ltd. | Unit 6a | Wakefield Business Centre Denby Dale Rd | Wakefield | WF2 7AZ | United Kingdom | ukinfo@dural.com

TECHNICAL DIMENSIONS AND PRODUCT VARIANTS

Material	[Aluminium]
Surface	[anodised]
Colour	silver, titanium
Length	100 cm, 270 cm
Width mm	38 mm

PRODUCT VARIANTS

Ident	Surface	Colour	Length
MXAE 3800/100	anodised	silver	100 cm
MXAE 3800-SK/100	anodised	silver	100 cm
MXAE 3800/270	anodised	silver	270 cm
MXAE 3800-SK/270	anodised	silver	270 cm
MXAE 3800-T/100	anodised	titanium	100 cm
MXAE 3800-T-SK/100	anodised	titanium	100 cm
MXAE 3800-T/270	anodised	titanium	270 cm
MXAE 3800-T-SK/270	anodised	titanium	270 cm

Please note: For technical reasons, tolerances in color effects of the materials and print are possible.
All information is based on the best of our knowledge and belief. No guarantee can be derived from this.
We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.

DURAL GmbH | Südring 11 | D-56412 Ruppach-Goldhausen | Germany | +49 2602/9261-0 | info@dural.com
DURAL Ltd. | Unit 6a | Wakefield Business Centre Denby Dale Rd | Wakefield | WF2 7AZ | United Kingdom | ukinfo@dural.com

The recognised standards and regulations of technology must be observed. Previous data sheets are invalid.