

SNAP LVT Expansion

Transition profile in aluminium with click assembly



PROPERTIES

Basic trim made of PVC for adhesive installation for covering heights of 5 - 7 mm

Top profile for clicking

MATERIAL

ABS/aluminium can be used wherever medium mechanical stress is to be expected. Contact with alkaline materials (e.g. tile adhesive) can cause discolouration that is almost impossible to remove. High humidity can intensify this process. Dirt deposits can be removed with standard cleaning agents. Cleaning agents must be free of abrasive powders or aggressive additives.

The suitability with regard to mechanical and chemical resistance must always be checked in each individual case.

CARE

Aluminium does not require any special care. If necessary, it can be cleaned with clear, clean water and a drop of washing-up liquid. Then wipe dry.

Avoid using acidic, alkaline and abrasive cleaning agents.

PROCESSING

1. Cut the profiles to size. The substrate must be cleaned of any contaminants such as release agents, preservatives, grease, oil, dust, water and old adhesives/sealants. Align the basic trim on the floor and stick it in place.
2. Secure the basic trim to the marked position using screws and dowels.
3. Lay the floor covering with sufficient expansion joint spacing.
4. Place the top profile on the basic trim.
5. Carefully tap the top profile into the base profile using a rubber mallet.
It will adjust to the respective height.

The generally accepted rules of technology and tiling must be observed. Suitability for use with mechanical and chemical resistance must always be checked in each individual case.

Please note: For technical reasons, tolerances in color effects of the materials and print are possible.
All information is based on the best of our knowledge and belief. No guarantee can be derived from this.
We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.



TECHNICAL DIMENSIONS AND PRODUCT VARIANTS

Material	[ABS],[Aluminium]
Surface	[anodised]
Colour	silver, champagne, titanium
Length	100 cm, 270 cm
sight width	44 mm
Height	5 mm
Width mm	44 mm
height up to	7 mm

PRODUCT VARIANTS

Ident	Height	Surface	Colour	Length
SNE LVT 600-C/100	5 mm	anodised	champagne	100 cm
SNE LVT 600-C/270	5 mm	anodised	champagne	270 cm
SNE LVT 600/100	5 mm	anodised	silver	100 cm
SNE LVT 600/270	5 mm	anodised	silver	270 cm
SNE LVT 600-T/100	5 mm	anodised	titanium	100 cm
SNE LVT 600-T/270	5 mm	anodised	titanium	270 cm

Please note: For technical reasons, tolerances in color effects of the materials and print are possible.
All information is based on the best of our knowledge and belief. No guarantee can be derived from this.
We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.