




SQUARELINE-LED

LED-illuminated edging profile for tiled and natural stone surfaces.



TECHNICAL DIMENSIONS AND PRODUCT VARIANTS

| | |
|-------------|--|
| Material | [Aluminium] |
| Surface | [powder coated], [anodised] |
| Colour | white, silver, champagne, black, titanium, black matt (RAL 9005) |
| Length | 250 cm |
| sight width | 10 mm, 12 mm |
| Height | 9 mm, 11 mm |

PRODUCT VARIANTS

| Ident | Height | Surface | Colour | Length |
|----------------------|--------|---------------|-----------------------|--------|
| SQLAE LED 90-SW/250 | 9 mm | anodised | black | 250 cm |
| SQLAE LED 90-C/250 | 9 mm | anodised | champagne | |
| SQLAE LED 90/250 | 9 mm | anodised | silver | 250 cm |
| SQLAE LED 90-T/250 | 9 mm | anodised | titanium | 250 cm |
| SQLACM LED 911/250 | 9 mm | powder coated | black matt (RAL 9005) | 250 cm |
| SQLAC LED 930/250 | 9 mm | powder coated | white | 250 cm |
| SQLAE LED 110-SW/250 | 11 mm | anodised | black | 250 cm |
| SQLAE LED 110-C/250 | 11 mm | anodised | champagne | |
| SQLAE LED 110/250 | 11 mm | anodised | silver | 250 cm |
| SQLAE LED 110-T/250 | 11 mm | anodised | titanium | 250 cm |
| SQLACM LED 1111/250 | 11 mm | powder coated | black matt (RAL 9005) | 250 cm |
| SQLAC LED 1130/250 | 11 mm | powder coated | white | 250 cm |

Data sheet Accessories

Suitable for all LED strips up to 8 mm width

Translucent covers in various colours, LED strips, switches and connection material are available as accessories.

We recommend using only original accessories from DURAL.

PROPERTIES

Suitable for all LED strips up to 8 mm width

Please note: For technical reasons, tolerances in color effects of the materials and print are possible. All information is based on the best of our knowledge and belief. No guarantee can be derived from this. We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.



MATERIAL

Aluminium/Polycarbonate can be used wherever medium mechanical loads are expected. Contact with alkaline materials (e.g. tile adhesive) can cause discolouration that is difficult to remove. High humidity during the drying phase can intensify this process. Always wipe tile adhesive or grout off visible surfaces immediately with plenty of water, then wipe dry and ensure good room ventilation.

The suitability with regard to mechanical and chemical resistance must always be checked in each individual case.

PROCESSING

1. Select the profile according to the tile thickness.
2. Apply tile adhesive with a notched trowel.
3. Press the profile into the adhesive bed and align it.
4. Fill the fixing flange completely with adhesive.
5. Press the tiles firmly into place and align them so that they are flush with the top edge of the profile. Lay the tiles so that they are completely covered.
6. Leave a 1-2 mm gap between the profile and the tiles.
7. Fill the space between the tiles and the profile completely with joint mortar.
8. Cut the LED strip to length at the designated points and carry out a function test.
9. Glue the LED strip centrally onto the diagonal bar in the profile and connect it.
10. Attach the translucent cover.

Protect visible surfaces from contact with tile adhesive or grout and clean immediately with a cloth and clear water if necessary. Then rub dry.

The generally accepted rules of technology and tiling must be observed. Suitability for use with mechanical and chemical resistance must always be checked in each individual case.

CARE

Aluminium/polycarbonate does not require any special care. If necessary, it can be cleaned with clear, clean water and a few drops of washing-up liquid. Then wipe dry.

Avoid using acidic, alkaline and abrasive cleaning agents.

Please note: For technical reasons, tolerances in color effects of the materials and print are possible.
All information is based on the best of our knowledge and belief. No guarantee can be derived from this.
We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.