




TACRIP EM-D

Single Rib Made Of Solid Stainless Steel For Outdoor Use According To German Standard



ACCESSORIES

Templates for standard installation of the single ribs are available as accessories.

PROPERTIES

Self adhesive.

Adhesive: 3M

For indoor areas on all floors except carpet.

Rib height: 4 mm

Rib length: 280 mm

Rib width: 12 mm

Rib surface: grooved

Slip resistance class: R9

MATERIAL

Stainless steel V2A/304 or V4A/316 is particularly suitable for applications subject to high mechanical stress and for applications with particularly high requirements for cleanliness, hygiene and chemical resistance. Contact with products containing hydrochloric acid should be avoided.

No tools made of unalloyed steel may be used for processing. Open cut edges are not rust-resistant. If necessary, separate rust protection must be applied there.

Even with stainless steel, flash rust may occur depending on the environmental conditions and should be removed immediately.

The suitability of the material with regard to mechanical and chemical resistance must always be checked in individual cases.

The suitability for mechanical and chemical stress must always be checked on a case-by-case basis.

CARE

Stainless steel (304) or (316) does not require any special care. If necessary, it can be cleaned with clear, clean water and a few drops of washing-up liquid. Then wipe dry.

Please note: For technical reasons, tolerances in color effects of the materials and print are possible. All information is based on the best of our knowledge and belief. No guarantee can be derived from this. We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.

DURAL GmbH | Südring 11 | D-56412 Ruppach-Goldhausen | Germany | +49 2602/9261-0 | info@dural.com

DURAL Ltd. | Unit 6a | Wakefield Business Centre Denby Dale Rd | Wakefield | WF2 7AZ | United Kingdom | ukinfo@dural.com

The recognised standards and regulations of technology must be observed. Previous data sheets are invalid.

www.dural.com



Avoid using acidic, alkaline and abrasive cleaning agents. Flash rust can be removed with commercially available polishes suitable for stainless steel.

PROCESSING

1. The substrate must be cleaned. Any contaminants such as release agents, preservatives, grease, oil, dust, water, old adhesives/sealants and other residues that could impair adhesion must be completely removed.
2. Mark the area where the film is to be placed.
3. Stick the template in the desired position on the floor.
4. We recommend using two connected templates (tongue and groove) at the start.
5. Remove the protective film from the back of the stud and stick it to the desired position using the template.
6. Continue with further studs as described in point 5 until the template is completely filled.
7. Press the studs down further by carefully walking over them with your feet.
8. Remove the template and press the nubs again by carefully walking over them with your feet.
9. If necessary, continue with step 3.

The generally accepted rules of technology and tiling must be observed. Suitability for use with mechanical and chemical resistance must always be checked in each individual case.

TECHNICAL DIMENSIONS AND PRODUCT VARIANTS

Material	[Stainless Steel (304)], [Stainless Steel (316L)]
Surface	[grooved]
Colour	natural
Length	28 cm, 280 cm
Height	4 mm
Width mm	12 mm

PRODUCT VARIANTS

Ident	Height	Surface	Colour	Length
TRE LG 12-3 SK V2A	4 mm	grooved	natural	28 cm
TRE LG 12-3 SK V4A	4 mm	grooved	natural	28 cm
TRE G 12-3 B V2A	4 mm	grooved	natural	280 cm
TRE G 12-3 B V4A	4 mm	grooved	natural	280 cm
TRE G 12-3 K V2A	4 mm	grooved	natural	280 cm
TRE G 12-3 K V4A	4 mm	grooved	natural	280 cm
TRE G 12-3 SK V2A	4 mm	grooved	natural	280 cm

Please note: For technical reasons, tolerances in color effects of the materials and print are possible. All information is based on the best of our knowledge and belief. No guarantee can be derived from this. We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.



TRE G 12-3 SK V4A	4 mm	grooved	natural	280 cm
TRE LG 12-3 B V2A	4 mm	grooved	natural	280 cm
TRE LG 12-3 B V4A	4 mm	grooved	natural	280 cm
TRE LG 12-3 K V2A	4 mm	grooved	natural	280 cm
TRE LG 12-3 K V4A	4 mm	grooved	natural	280 cm

Please note: For technical reasons, tolerances in color effects of the materials and print are possible.
 All information is based on the best of our knowledge and belief. No guarantee can be derived from this.
 We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.